Registration Information Carbon Footprint of Products (CFP)



1. Pro	1. Product information					
1.1	Registration number	CR-DG02-17043	1.7 Product photo			
1.2	Registration name	Xerox AltaLink C8070				
1.3	Model name / number	Xerox AltaLink C8070				
1.4	Main specifications of product	Print speed (Color/Mono): 70ppm/70ppm (Letter) Maximum Paper size: SRA3(320x450mm) Capable of print/copy/scan/fax, duplex printing. Product Size: 640(W)x732.8(D)x1142.7(H) (mm) Product weight: 148.9kg				
1.5	CFP quantification unit	Per unit product				
1.6	CFP release date	May 8th, 2017				

2. Con	2. Company Information				
2.1	Company name (in English)	Fuji Xerox Co., Ltd.			
2.2	Phone number (incl. area code)	+81-3-6271-5111			

3. CFF	CFP quantification results, and description of CFP deciration					
3.1	CFP quantification results	5,100	kg-CO2e			
	Breakdown (by life cyc	le stage, by process, by flow, etc.)				
	Raw material acquisition stage	910	kg-CO ₂ e			
3.2	Production stage	20	kg-CO ₂ e			
3.2	Distribution stage	160	kg-CO ₂ e			
	Use & maintenance stage	3,900	kg-CO ₂ e			
	Disposal & recycling stage	71	kg-CO ₂ e			
	Value in CFP mark and d	escription of additional info.				
		<numerial value=""></numerial>	<unit for="" the="" value=""></unit>			
	Value in CFP mark	5,100kg	per unit product			
3.3	Description of additional info.	5,100kgper unit productCalculated by the standard Scenario for MFP (EP type).CO2 emission in the distribution stage assumes the United States as the main sales area.Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption-rate in the United States.Print volume is assumed 2,940,000 sheets.In this scenario, the CO2 emissions from copy papers are estimated 23,000 kg- CO2e at 4.0g per A4 paper.The CO2 emission of printing paper is excluded from the use and maintenance stage.Disposal & recycling stage 2%Use & maintenance stage 77%				
3.4	Remarks					
5.4	INCIII di NO					

4. Interpretation of CFP quantification results					
4. Inte	Interpretation of CFP quantification results	CO2 emission in use and maintenance stage is the largest as 77%. It is important to save energy during product usage. The use condition in this scenario can be different from the use condition of the user. A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during product usage. For example, 975kg-CO2e of the CO2 emissions (approximately 19%) can be reduced if 2-in-1 print is applied to 50% of the estimated total print volume. Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as the rough estimate according to the reason			

5. Cor	5. Conditions of quantification				
5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-02
5.3	Assumptions of	Basic secondary data v.1.01 is preferentially used. Available secondary data (country v.1.04, foreign country v.1.01) is used if the items don't correspond to basic data v.1.01.			

6. Veri	6. Verification information				
6.1	Verification method	Product-by-product	6.2	CFP system certification No.	_
6.3	Verification ID	CV-DG02-17043	6.4	Completion date of verification	April 28th, 2017

7. Pro	7. Program information				
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	<u>http://www.cfp-japan.jp/</u>
7.3	Program operator	Japan Environmental Management Association for Industry (JEMAI)	7.4	Address	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

8	Remarks	_			
For oor	For according data, places refer to the information on the following CFD website				

For secondary data, please refer to the information on the following CFP website. http://www.cfp-japan.jp/calculate/verify/data.html