Registration Information Carbon Footprint of Products (CFP)



1. Pro	duct information		
1.1	Registration number	CR-DG01-16044	1.7 Product photo
1.2	Registration name	ApeosPort-V C7785 (For Taiwan)	1
1.3	Model name / number	ApeosPort-V C7785	
1.4	Main specifications of product	Print speed (Color/Mono): 70ppm/75ppm Paper size: SRA3(320x450mm) maximum Capable of duplex printing, facsimile and scanning Product Size: 700(W)x804(D)x1154(H) (mm) Product weight: 240kg	
1.5	CFP quantification unit	Per unit product	10.00 At 10
1.6	CFP release date	2016/7/12	

2. Cor	mpany Information	
2.1	Company name (in English)	Fuji Xerox Co., Ltd.
2.2	Phone number (incl. area code)	+81-3-6271-5111

3. CFF	P quantification results, ar	d description of CFP declration	
3.1	CFP quantification results	6,800	kg-CO2e
	Breakdown (by life cyc	le stage, by process, by flow, etc.)	
	Raw material acquisition stage	1,300	kg-CO₂e
3.2	Production stage	100	kg-CO ₂ e
5.2	Distribution stage	33	kg-CO ₂ e
	Use & maintenance stage	5,200	kg-CO ₂ e
	Disposal & recycling stage	82	kg-CO ₂ e
	Value in CFP mark and c	lescription of additional info.	
		<numerial value=""></numerial>	<unit for="" the="" value=""></unit>
	Value in CFP mark	6,800 kg	per unit product
3.3	Description of additional info.	*Calculated by the standard So *CO ₂ emission in the distribution assumes Taiwan as the main sales area. *Electric power in the use and maintenance stage is evaluate the public electric-power-conso -rate in Taiwan. *The CO ₂ emission due to prin paper is excluded from the use and maintenance stage. *Print volume is assumed 2,94	ad with umption ting e 77%
3.4	Remarks	*Print volume: 2,940,000 sheets *In this scenario, the CO_2 emissic 4.0 g per A4 paper.	ons from copy papers are estimated 23,000 kg-CO $_{2}$ e at

4. Inte	rpretation of CFP quantifi	cation results
4.1	Interpretation of CFP quantification results	CO2 emission in use and maintenance stage is the largest as 77%. It is important to save energy during product usage. The use condition in this scenario can be different from the use condition of the user. A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during product usage. For example, 1303kg-CO2e of the CO2 emissions (approximately 19%) can be reduced if 2-in-1 print is applied to 1,470,000sheets (50% of print volume). Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as the rough estimate according to the reason mentioned above.

5. Cor	ditions of quantification				
5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-01
5.3	Assumptions of	Basic secondary data v.1. (country v.1.04, foreign co basic data v.1.01.			-

6. Ver	ification information				
6.1	Verification method	Product-by-product	6.2	CFP system certification No.	_
6.3	Verification ID	CV-DG01-16044	6.4	Completion date of verification	2016/7/5

7. Pro	gram information				
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	<u>http://www.cfp-japan.jp/</u>
7.3	Program operator	Japan Environmental Management Association for Industry (JEMAI)	7.4	Address	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

8 Remarks –

For secondary data, please refer to the information on the following CFP website. http://www.cfp-japan.jp/calculate/verify/data.html