## Registration information of Carbon Footprint of Products

1. Pro	duct information		
1.1	Registration number	CR-DG01-14008-A	1.7 Product photo
1.2	Product name	Dell C2665dnf Color Laser Multifunction Printer	
1.3	Product model	Product model Dell C2665dnf Color Laser Multifunction Printer	
1.4	Main specifications of product	Print speed (Letter/A4): 27ppm color/black-and-white Paper size: A4 maximum Capable of duplex printing and facsimile Product Size: 439(W)x529.5(D)x558(H) (mm) Product weight: 32.6kg	0
1.5	CFP quantification unit	Per unit product	
1.6	Date of release	2014/3/4	

2. Company Information			
2.1	Company name	FUJIFILM Business Innovation Corp.	
2.2	Phone number	+81-3-6271-5111	

3. CFF	o quantification results, ar	d contents of CFP deciration		
3.1	CFP quantification results	1,500	kg-CO <sub>2</sub> e (CFP quantification results can be slightly different from sum of thefollowing breakdown for rounding of fractions.)	
	Breakdown (by life cycle stage, by process, by flow, etc.)			
	Raw material acquisition stage	210	kg-CO <sub>2</sub> e	
3.2	Production stage	28	kg-CO <sub>2</sub> e	
3.2	Distribution stage	23	kg-CO <sub>2</sub> e	
	Use & maintenance stage	1,200	kg-CO₂e	
	Disposal & recycling stage	67	kg-CO <sub>2</sub> e	
	Value in a mark, and co	ntents of additional info.		
		<contents></contents>	<unit a="" for="" in="" mark="" the="" value=""></unit>	
	Value in a mark	1,500 kg	per unit product	
3.3	*Scenario: Printer (EP type)  *The CO2 emission due to prise papers is excluded from the use and maintenance stage.  *Print volume: 437,000 sheet:  *CO2 emission in the distribution stage assumes North America as the main sales area.  *Electric power in the use and electric-power-consumption-		Distribution stage Use & maintenance stage (78%) Disposal & recycling stage  maintenance stage is evaluated with the public	
3.4	Remarks	*Print volume: $437,000$ sheets *In this scenario, the $CO_2$ emissions from copy papers are estimated $3,400$ kg- $CO_2$ e at $4.0$ g per A4 paper.		

4. Interpretation of CFP quantification results					
4.1	Interpretation of CFP quantification results	CO <sub>2</sub> emission in use and maintenance stage is the largest as 78%. It is important to save energy during product usage. The use condition in this scenario can be different from the use condition of the user.  A choice of the use condition (print mode, print conditions and so on) can reduce the CO <sub>2</sub> emission during product usage. For example, 185kg-CO <sub>2</sub> e of the CO <sub>2</sub> emissions (approximately 12%) can be reduced if 2-in-1 print is applied to 219,000sheets (50% of print volume).  CO <sub>2</sub> emission in raw material acquisition stage is the second largest as 14%. It is also important to reduce size and weight.  Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as the rough estimate according to the reason mentioned above.			

I	5. Conditions of quantification					
I	5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-01
	5.3		Basic secondary data v.1.01 is preferentially used. Available secondary data (country v.1.04, foreign country v.1.01) is used if the items don't correspond to basic data v.1.01.			

6. Verification information					
6.1	Verification method	Product-by-product	6.2	CFP system certification No.	-
6.3	Verification ID	CV-DG01-14008	6.4	Completion date of verification	2014/2/21

7 Remarks Revised on April 1st, 2021: Implemented the company name c	hange.
--	--------

<sup>(\*)</sup> For secondary data, refer to the following page on the CFP website.  $\label{eq:cfp} {\tt http://www.cfp-japan.jp/calculate/verify/data.html}$