## Registration Information Carbon Footprint of Products (CFP)



1. Product information				
1.1	Registration number	CR-DG01-15002-A	1.7 Product photo	
1.2	Product name	Dell Color Printer C3760		
1.3	Product model	Dell Color Printer C3760		
1.4	Main specifications of product	Print speed (Letter/A4): 36ppm color/black-andwhite Paper size: A4 maximum Capable of duplex printing Product Size: 439(W)x485(D)x379(H) (mm) Product weight: 25.6kg		
1.5	CFP quantification unit	Per unit product		
1.6	Date of release	2015/3/19		

2. Company Information			
2.1	Company name	FUJIFILM Business Innovation Corp.	
2.2	Phone number	+81-3-6271-5111	

3. CFP quantification results, and description of CFP declration				
3.1	CFP quantification results	2,300	kg-CO2e (CFP quantification results can be slightly different from sum of thefollowing breakdown for rounding of fractions.)	
		le stage, by process, by flow, etc.)		
	Raw material acquisition stage	150	kg-CO₂e	
3.2	Production stage	28	kg-CO <sub>2</sub> e	
3.2	Distribution stage	19	kg-CO <sub>2</sub> e	
	Use & maintenance stage	2,000	kg-CO <sub>2</sub> e	
	Disposal & recycling stage	43	kg-CO <sub>2</sub> e	
	Value in CFP mark and description of additional info.			
	Value in a mark	<numerial value=""></numerial>	<unit for="" the="" value=""></unit>	
		2,300 kg	per unit product	
3.3	Contents of additional info.	<ul> <li>*Calculated by the standard Scenario for Printer (EP type)</li> <li>*CO2 value is evaluated on the C3760dn model with automatic duplex printingfunction.</li> <li>The difference from C3760n without automatic duplex printing is less than 1% throughout the life cycle. No difference in the CO2 value in the use and maintenance stage.</li> <li>*CO2 emission in the distribution stage assumes North America as the main sales area.</li> <li>*Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption -rate in North America.</li> <li>*The CO2 emission due to printing paper is excluded from the use and maintenance stage.</li> <li>*Print volume is assumed 777,600 sheets.</li> </ul>		
3.4	Remarks	*Print volume: 777,600 sheets Remarks *In this scenario, the CO2 emissions from copy papers are estimated 6,000 kgCO2e at 4.0 g per A4 paper.		

4. Interpretation of CFP quantification results				
4.1		CO2 emission in use and maintenance stage is the largest as 89%. It is important to save energy during product usage. The use condition in this scenario can be different from the use condition of the user. A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during product usage. For example, 385kg-CO2e of the CO2 emissions (approximately 17%) can be reduced if 2-in-1 print is applied to 388,800sheets (50% of print volume). CO2 emission in raw material acquisition stage is the second largest as 12%. It is also important to reduce size and weight. Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as the rough estimate according to the reason mentioned above.		

5. Conditions of quantification					
5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-01
5.3	Assumptions of	Basic secondary data v.1 (country v.1.04、foreign country v			ailable secondary data n't correspond to basic data

6. Verification information					
6.1	Verification method	Product-by-product	6.2	CFP system certification No.	_
6.3	Verification ID	CV-DG01-15002	6.4	Completion date of verification	2015/3/10

	7	Remarks	Revised on April 1st, 2021: Implemented the company name change.
--	---	---------	------------------------------------------------------------------

(\*) For secondary data, refer to the following page on the CFP website. http://www.cfp-japan.jp/calculate/verify/data.html

L