Registration information of Carbon Footprint of Products

1. Product information				
1.1	Registration number	CR-DG01-15005-A	1.7 Product photo	
1.2	Product name	Xerox WorkCentre 5335 Copier STD		
1.3	Product model	Xerox WorkCentre 5335 Copier STD		
1.4	Main specifications of product	Print speed: 35ppm black-and-white Paper size: A3 maximum Capable of duplex printing Product Size: 597(W)x637.5(D)x1115(H) (mm) Product weight: 85kg		
1.5	CFP quantification unit	Per unit product		
1.6	Date of release	-		

2. Company Information				
2.1 Company name FUJIFILM Business Innovation Corp.		FUJIFILM Business Innovation Corp.		
2.	.2	Phone number	+81-3-6271-5111	

3. CFF	3. CFP quantification results, and contents of CFP declration				
3.1	CFP quantification results	1,600	kg-CO ₂ e (CFP quantification results can be slightly different from sum of thefollowing breakdown for rounding of fractions.)		
	Breakdown (by life cycle stage, by process, by flow, etc.)				
	Raw material acquisition stage	620	kg-CO₂e		
3.2	Production stage	34	kg-CO₂e		
3.2	Distribution stage	50	kg-CO₂e		
	Use & maintenance stage	750	kg-CO₂e		
	Disposal & recycling stage	99	kg-CO₂e		
	Value in a mark, and co	ntents of additional info.			
		<contents></contents>	<unit a="" for="" in="" mark="" the="" value=""></unit>		
	Value in a mark	Value in a mark 1,600 kg per unit product			
additional info. the public electric-power-consumption -rate in North America. *The CO2 emission due to printing paper is excluded from the use and maintenance stage.		e main Raw material acquisition stage Production stage Distribution stage Use & maintenance stage			
3.4	Remarks				

4. Interpretation of CFP quantification results					
4.1	Interpretation of CFP quantification results	CO ₂ emission in use and maintenance stage is the largest as 48%. It is important to save energy during product usage. The use condition in this scenario can be different from the use condition of the user. A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during product usage. CO ₂ emission in raw material acquisition stage is the second largest as 40%. It is also important to reduce size and weight. Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as the rough estimate according to the reason mentioned above.			

5. Con	Conditions of quantification				
5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-01
5.3		Basic secondary data v.1.01 is preferentially used. Available secondary data (country v.1.04, foreign country v.1.0) is used if the items don't correspond to basic data v.1.01.			

6. Verification information					
6.1	Verification method	Product-by-product	6.2	CFP system certification No.	_
6.3	Verification ID	CV-DG01-15005	6.4	Completion date of verification	2015/3/13

7	Remarks	Revised on April 1st, 2021: Implemented the company name change.

^(*) For secondary data, refer to the following page on the CFP website. http://www.cfp-japan.jp/calculate/verify/data.html