## Registration information of Carbon Footprint of Products

1. Product information				
1.1	Registration number	CR-DG01-15006-A	1.7 Product photo	
1.2	Product name	Xerox WorkCentre 5325 Multifunction Printer STD		
1.3	Product model	Xerox WorkCentre 5325 Multifunction Printer STD	I I man g	
1.4	Main specifications of product	' L'anable of dilbiey brinting facsimile and scanning		
1.5	CFP quantification unit	Per unit product	4	
1.6	Date of release	2015/3/24	•	

2. Company Information				
2.1 Company name FUJIFILM Business Innovation Corp.		FUJIFILM Business Innovation Corp.		
2.	.2	Phone number	+81-3-6271-5111	

2 000	3. CFP quantification results, and contents of CFP declration				
3. CFF	CFP quantification results, and compared to the compared to th	1,300	kg-CO <sub>2</sub> e (CFP quantification results can be slightly different from sum of		
		thefollowing breakdown for rounding of fractions.) by life cycle stage, by process, by flow, etc.)			
	Raw material acquisition stage	620	kg-CO₂e		
0.0	Production stage	34	kg-CO₂e		
3.2	Distribution stage	50	kg-CO₂e		
	Use & maintenance stage	500	kg-CO₂e		
	Disposal & recycling stage	99	kg-CO₂e		
	Value in a mark, and co	ntents of additional info.			
		<contents></contents>	<unit a="" for="" in="" mark="" the="" value=""></unit>		
	Value in a mark	1,300 kg	per unit product		
3.3	Contents of additional info.	*Calculated by the standard Scenario for Multifunction Printer (EP type)  *CO2 emission in the distribution stage assumes North America as the main sales area.  *Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption -rate in North America.  *The CO2 emission due to printing paper is excluded from the use and maintenance stage.  *Print volume is assumed 375,000 sheets.			
3.4	Remarks				

4. Interpretation of CFP quantification results				
4.1	Interpretation of CFP quantification results	CO <sub>2</sub> emission in raw material acquisition stage is the largest as 47%. It is also important to reduce size and weight.  The use condition in this scenario can be different from the use condition of the user.  A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during product usage.  CO <sub>2</sub> emission in use and maintenance stage is the second largest as 38%. It is important to save energy during product usage.  Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as the rough estimate according to the reason mentioned above.		

5	. Con	Conditions of quantification				
	5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-01
Assumptions of secondary data used  Assumptions of secondary data used  Basic secondary data v.1.01 is preferentially used. Available secondary v.1.04, foreign country v.1.0) is used if the items don't correspond to be						

6. Verification information					
6.1	Verification method	Product-by-product	6.2	CFP system certification No.	_
6.3	Verification ID	CV-DG01-15006	6.4	Completion date of verification	2015/3/13

7	Remarks	Revised on April 1st, 2021: Implemented the company name change.

<sup>(\*)</sup> For secondary data, refer to the following page on the CFP website. http://www.cfp-japan.jp/calculate/verify/data.html