Registration Information Carbon Footprint of Products (CFP)



1. Pro	1. Product information				
1.1	Registration number	CR-DG01-15029-A	1.7 Product photo		
1.2	Product name	ell Color Cloud Multifunction Printer H625cdw			
1.3	Model name / number	Dell Color Cloud Multifunction Printer H625cdw			
1.4	Main specifications of product				
1.5	CFP quantification unit	Per unit product			
1.6	CFP release date	2015/10/29			

2. Company Information				
2.1	Company name (in English)	FUJIFILM Business Innovation Corp.		
2.2	Phone number (incl. area code)	+81-3-6271-5111		

3. CFF	3. CFP quantification results, and description of CFP declration					
3.1	CFP quantification results	1,200	kg-CO2e			
	Breakdown (by life cycle stage, by process, by flow, etc.)					
	Raw material acquisition stage	180	kg-CO₂e			
	Production stage	25	kg-CO₂e			
3.2	Distribution stage	21	kg-CO₂e			
	Use & maintenance stage	910	kg-CO ₂ e			
	Disposal & recycling stage	47	kg-CO ₂ e			
	Value in CFP mark and o	lescription of additional info.				
	Value to be stated on the mark	<numerial value=""></numerial>	<unit for="" the="" value=""></unit>			
		1,200 kg	per unit product			
3.3	Description of additional info.	*Calculated by the standard Scenario for Printer (EP type) *CO2 emission in the distribution stage assumes North America as the main sales area. *Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption -rate in North America. *The CO2 emission due to printing paper is excluded from the use and maintenance stage. *Print volume is assumed 375,000 sheets.				
3.4	Remarks	*Print volume: 375,000 sheets *In this scenario, the CO2 emissions from copy papers are estimated 2,900 kg-CO2e at 4.0				

4. Inte	4. Interpretation of CFP quantification results					
4.1		CO2 emission in use and maintenance stage is the largest as 77%. It is important to save energy during product usage. The use condition in this scenario can be different from the use condition of the user. A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during product usage. For example, 227kg-CO2e of the CO2 emissions (approximately 19%) can be reduced if 2-in-1 print is applied to 187,500sheets (50% of print volume). Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as the rough estimate according to the reason mentioned above.				

5. Cor	5. Conditions of quantification				
5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-01
	Assumptions of secondary data used	Basic secondary data v.1.01 is preferertially used. Available secondary data			
5.3		(country v.1.04、foreign country v.1.01) is used if the items don't correspond to			
		basic data v.1.01.			

6. Verification information					
6.1	Verification method	Product-by-product	6.2	CFP system certification No.	_
6.3	Verification ID	CV-DG01-15029	6.4	Completion date of verification	2015/10/13

7. Pro	7. Program information				
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	http://www.cfp-japan.jp
7.3	Program operator	Japan Environmental Management Association for Industry (JEMAI)	7.4	Address	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

8	Remarks	Revised on April 1st, 2021: Implemented the company name change.

For secondary data, please refer to the information on the following CFP website. http://www.cfp-japan.jp/calculate/verify/data.html