Registration Information Carbon Footprint of Products (CFP)



1. Pro	1. Product information						
1.1	Registration number	CR-DG01-16044-A	1.7 Product photo				
1.2	Registration name	ApeosPort- V C7785 (For Taiwan)					
1.3	Model name / number	ApeosPort- V C7785					
1.4	Main specifications of productPrint speed (Color/Mono): 70ppm/75ppm Paper size: SRA3(320x450mm) maximum Capable of duplex printing, facsimile and scanning Product Size: 700(W)x804(D)x1154(H) (mm) Product weight: 240kg						
1.5	CFP quantification unit	Per unit product					
1.6	CFP release date	2016/7/12					

2. Co	2. Company Information					
2.1	Company name (in English)	FUJIFILM Business Innovation Corp.				
2.2	Phone number (incl. area code)	+81-3-6271-5111				

3. CFF	3. CFP quantification results, and description of CFP declration					
3.1	CFP quantification results	6,800	kg-CO2e			
	Breakdown (by life cyc	le stage, by process, by flow, etc.)				
	Raw material acquisition stage	1,300	kg-CO₂e			
3.2	Production stage	100	kg-CO ₂ e			
5.2	Distribution stage	33	kg-CO₂e			
	Use & maintenance stage	5,200	kg-CO₂e			
	Disposal & recycling stage	82	kg-CO₂e			
	Value in CFP mark and o	lescription of additional info.				
		<numerial value=""></numerial>	<unit for="" the="" value=""></unit>			
	Value in CFP mark	6,800 kg	per unit product			
3.3	 ³ Calculated by the standard Scenario for MFP (EP type) [*]CO₂ emission in the distribution stage assumes Taiwan as the main sales area. [*]Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption -rate in Taiwan. [*]The CO₂ emission due to printing paper is excluded from the use and maintenance stage. [*]Print volume is assumed 2,940,000 sheets. 					
3.4	Remarks	*Print volume: 2,940,000 sheets *In this scenario, the CO ₂ emissions from copy papers are estimated 23,000 kg-CO ₂ e at 4.0 g per A4 paper.				

4. Inte	. Interpretation of CFP quantification results				
4.1	Interpretation of CFP quantification results	CO2 emission in use and maintenance stage is the largest as 77%. It is important to save energy during product usage. The use condition in this scenario can be different from the use condition of the user. A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during product usage. For example, 1303kg-CO2e of the CO2 emissions (approximately 19%) can be reduced if 2-in-1 print is applied to 1,470,000sheets (50% of print volume). Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as the rough estimate according to the reason mentioned above.			

5. Cor	litions of quantification				
5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-01
5.3	Assumptions of	Basic secondary data v.1.01 is preferertially used. Available secondary data (country v.1.04, foreign country v.1.01) is used if the items don't correspond to basic data v.1.01.			

6. Verification information					
6.1	Verification method	Product-by-product	6.2	CFP system certification No.	—
6.3	Verification ID	CV-DG01-16044	6.4	Completion date of verification	2016年7月5日

7. Pro	Program information				
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	<u>http://www.cfp-japan.jp/</u>
7.3	Program operator	Japan Environmental Management Association for Industry (JEMAI)	7.4	Address	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

		8	Remarks	Revised on April 1st, 2021: Implemented the company name change.
--	--	---	---------	--

For secondary data, please refer to the information on the following CFP website. http://www.cfp-japan.jp/calculate/verify/data.html