## Registration Information Carbon Footprint of Products (CFP)



1. Pro	. Product information							
1.1	Registration number	CR-DG01-16045-A	1.7 Product photo					
1.2	Registration name	Registration name ApeosPort-V C7785 (For Japan)						
1.3	Model name / number	ApeosPort-V C7785						
1.4	Main specifications of product	Print speed (Color/Mono): 70ppm/75ppm Paper size: SRA3(320x450mm) maximum Capable of duplex printing, facsimile and scanning Product Size: 700(W)x804(D)x1154(H) (mm) Product weight: 240kg						
1.5	CFP quantification unit	CFP quantification unit Per unit product						
1.6	CFP release date	2016/7/12						

ı	2. Company Information					
	2.1	Company name (in English)	FUJIFILM Business Innovation Corp.			
	2.2	Phone number (incl. area code)	+81-3-6271-5111			

3. CFF	3. CFP quantification results, and description of CFP declration							
3.1	CFP quantification results	6,200	kg-CO2e					
	Breakdown (by life cycle stage, by process, by flow, etc.)							
	Raw material acquisition stage	1,300	kg-CO₂e					
3.2	Production stage	100	kg-CO₂e					
3.2	Distribution stage	43	kg-CO₂e					
	Use & maintenance stage	4,700	kg-CO <sub>2</sub> e					
	Disposal & recycling stage	63	kg-CO₂e					
	Value in CFP mark and o	lescription of additional info.						
		<numerial value=""></numerial>	<unit for="" the="" value=""></unit>					
	Value in CFP mark	6,200 kg	per unit product					
3.3		*Calculated by the standard Scenario for MFP (EP type) *CO <sub>2</sub> emission in the distribution stage assumes Japan as the main sales area. *Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption -rate in Japan. *The CO <sub>2</sub> emission due to printing paper is excluded from the use and maintenance stage. *Print volume is assumed 2,940,000 sheets.  *Disposal & recycling stage						
3.4	Remarks	*Print volume: 2,940,000 sheets *In this scenario, the $CO_2$ emissions from copy papers are estimated 23,000 kg- $CO_2$ e at 4.0 g per A4 paper.						

A later worth from a COED was self-order words.									
4. Inte	4. Interpretation of CFP quantification results								
4.1	Interpretation of CFP quantification results	CO2 emission in use and maintenance stage is the largest as 76%. It is important to save energy during product usage. The use condition in this scenario can be different from the use condition of the user.  A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during product usage. For example, 1,170kg-CO2e of the CO2 emissions (approximately 19%) can be reduced if 2-in-1 print is applied to 1,470,000sheets (50% of print volume).  Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as the rough estimate according to the reason mentioned above.							
5. Cor	nditions of quantification								
5.1		Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-01				
5.3	Assumptions of secondary data used	Basic secondary data v.1.01 is preferertially used. Available secondary data (country v.1.04, foreign country v.1.01) is used if the items don't correspond to basic data v.1.01.							
6. Ver	ification information								
6.1	Verification method	Product-by-product	6.2	CFP system certification No.	-				
6.3	Verification ID	CV-DG01-16045	6.4	Completion date of verification	2016年7月5日				

8 Remarks Revised on April 1st, 2021: Implemented the company name change.

7.2

7.4

Web site

Address

http://www.cfp-japan.jp/

Tokyo 101-0044

2-1, Kajicho 2-chome, Chiyoda-ku,

For secondary data, please refer to the information on the following CFP website. http://www.cfp-japan.jp/calculate/verify/data.html

Carbon Footprint

Industry (JEMAI)

Communication Program

Japan Environmental

. Management Association for

7. Program information

Program name

Program operator

7.1

7.3