Registration Information Carbon Footprint of Products (CFP)



1. Pro	duct information		
1.1	Registration number	CR-DG02-17038-A	1.7 Product photo
1.2	Registration name	Xerox AltaLink C8030	
1.3	Model name / number	Xerox AltaLink C8030	
1.4	Main specifications of product	Print speed (Color/Mono): 30ppm/30ppm (Letter) Maximum Paper size: SRA3(320x450mm) Capable of print/copy/scan/fax, duplex printing. Product Size: 640(W)x732.8(D)x1142.7(H) (mm) Product weight: 143.4kg	
1.5	CFP quantification unit	Per unit product	
1.6	CFP release date	May 8th, 2017	

2. Company Information			
2.1	Company name (in English) FUJIFILM Business Innovation Corp.		
2.2	Phone number (incl. area code)	+81-3-6271-5111	

2 CEL	CFP quantification results, and description of CFP declration				
	CFP quantification	·			
3.1	results	2,000	kg-CO2e		
		e stage, by process, by flow, etc.)			
	Raw material acquisition stage	850	kg-CO₂e		
3.2	Production stage	20	kg-CO ₂ e		
3.2	Distribution stage	160	kg-CO ₂ e		
	Use & maintenance stage	880	kg-CO ₂ e		
	Disposal & recycling stage	66	kg-CO₂e		
	Value in CFP mark and d	escription of additional info.			
		<numerial value=""></numerial>	<unit for="" the="" value=""></unit>		
	Value in CFP mark	2,000kg	per unit product		
3.3	Description of additional info.	*Calculated by the standard Scenario for MFP (EP type). *CO ₂ emission in the distribution stage assumes the United States as the main sales area. *Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption-rate in the United States. *Print volume is assumed 540,000 sheets. *In this scenario, the CO ₂ emissions from copy papers are estimated 4,200 kg-CO ₂ e at 4.0g per A4 paper. *The CO ₂ emission of printing paper is excluded from the use and maintenance stage. Disposal & recycling stage 3% Raw material acquisition stage 43% Distribution stage 1%			
3.4	Remarks				
J.4	Remarks				

4. Inte	terpretation of CFP quantification results				
		CO_2 emission in use and maintenance stage is the largest as 45%. It is important to save energy during product usage.			
4.1	Interpretation of CFP quantification results	The use condition in this scenario can be different from the use condition of the user. A choice of the use condition (print mode, print conditions and so on) can reduce the $\rm CO_2$ emission during product usage. For example, 218.3kg- $\rm CO_2$ e of the $\rm CO_2$ emissions (approximately 11%) can be reduced if 2-in-1 print is applied to 50% of the estimated total print volume. Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as the rough estimate according to the reason mentioned above.			

	5. Con	onditions of quantification				
I	5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-02
ľ	5.3	Assumptions of	Basic secondary data v.1.01 is preferentially used. Available secondary data (country v.1.04, foreign country v.1.01) is used if the items don't correspond to basic data v.1.01.			

6. Ver	erification information				
6.1	Verification method	Product-by-product	6.2	CFP system certification No.	_
6.3	Verification ID	CV-DG02-17038	6.4	Completion date of verification	April 28th, 2017

7. Pro	Program information				
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	http://www.cfp-japan.jp/
7.3	Program operator	Japan Environmental Management Association for Industry (JEMAI)	7.4	Δαατρος	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

I	8	Remarks	Revised on April 1st. 2021: Implemented the company name change.
		Remarks	revised on April 13t, 2021. Implemented the company hame change.

For secondary data, please refer to the information on the following CFP website. http://www.cfp-japan.jp/calculate/verify/data.html