Registration Information Carbon Footprint of Products (CFP)



1. Pro	1. Product information						
1.1	Registration number	CR-DG02-17053-A	1.7 Product photo				
1.2	Registration name	Xerox VersaLink B7035 Multifunction Printer (1TM)					
1.3	Model name / number	Xerox VersaLink B7035 Multifunction Printer (1TM)					
1.4	Main specifications of product	Print speed (Mono): 35ppm (A4) Maximum Paper size: A3(297×420mm) Capable of print/copy/scan/fax, duplex printing, WiFi, NFC. Product Size: 615.7(W)x670.8(D)x1118.6(H) (mm) Product weight: 76kg					
1.5	CFP quantification unit	Per unit product	3				
1.6	CFP release date	May 19th, 2017					

2. Company Information					
2.1	Company name (in English)	FUJIFILM Business Innovation Corp.			
2.2	Phone number (incl. area code)	+81-3-6271-5111			

3. CFF	. CFP quantification results, and description of CFP declration						
3.1	CFP quantification results	1,600	kg-CO2e				
	Breakdown (by life cyc	le stage, by process, by flow, etc.)					
	Raw material acquisition stage	330	kg-CO₂e				
3.2	Production stage	10	kg-CO ₂ e				
3.∠	Distribution stage	91	kg-CO₂e				
	Use & maintenance stage	1,100	kg-CO₂e				
	Disposal & recycling stage	33	kg-CO₂e				
	Value in CFP mark and o	lescription of additional info.					
		<numerial value=""></numerial>	<unit for="" the="" value=""></unit>				
	Value in CFP mark	1,600kg	per unit product				
3.3	Description of additional info.	*Calculated by the standard Scenario for MFP (EP type). *CO ₂ emission in the distribution stage assumes the United States as the main sales area. *Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption-rate in the United States. *Print volume is assumed 735,000 sheets. *In this scenario, the CO ₂ emissions from copy papers are estimated 5,670 kg-CO ₂ e at 4.0g per A4 paper. *The CO ₂ emission of printing paper is excluded from the use and maintenance stage. Disposal & recycling stage 2% Production stage 1% Use & maintenance stage 70% Distribution stage 6%					
3.4	Remarks						
3.4	Remarks						

4. Inte	4. Interpretation of CFP quantification results					
		CO2 emission in use and maintenance stage is the largest as 70%. It is important to save energy during product usage. The use condition in this scenario can be different from the use condition of the				
4.1	Interpretation of CFP quantification results	user. A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during product usage. For example, 272.5kg-CO2e of the CO2 emissions (approximately 18%) can be reduced if 2-in-1 print is applied to 50% of the estimated total print volume.				
		Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as the rough estimate according to the reason mentioned above.				

L	5. Conditions of quantification					
	5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-02
	5.3	Assumptions of secondary data used	-	Basic secondary data v.1.01 is preferertially used. Available secondary data country v.1.04, foreign country v.1.01) is used if the items don't correspond to pasic data v.1.01.		

6. Veri	6. Verification information					
6.1	Verification method	Product-by-product	6.2	CFP system certification No.	-	
6.3	Verification ID	CV-DG02-17053	6.4	Completion date of verification	May 12th, 2017	

7. Pro	7. Program information				
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	http://www.cfp-japan.jp/
7.3	Program operator	Japan Environmental Management Association for Industry (JEMAI)	7.4	Address	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

8	Remarks	Revised on April 1st, 2021: Implemented the company name change.

For secondary data, please refer to the information on the following CFP website. http://www.cfp-japan.jp/calculate/verify/data.html