## Registration Information Carbon Footprint of Products (CFP)



1. Pro	1. Product information								
1.1	Registration number	CR-DG02-17068-A	1.7 Product photo						
1.2	Registration name	Xerox VersaLink C500 Color Printer							
1.3	Model name / number								
1.4	Main specifications of product	Print speed (Color/Mono): 45ppm/45ppm (Letter) Maximum Paper size: Legal(215.9×355.6mm) Capable of print, duplex printing, NFC. Product Size: 427.4(W)x465.5(D)x443.4(H) (mm) Product weight: 27.6kg	See						
1.5	CFP quantification unit	Per unit product							
1.6	CFP release date	July 14th, 2017							

2. Co	2. Company Information					
2.1	Company name (in English)	FUJIFILM Business Innovation Corp.				
2.2	Phone number (incl. area code)	+81-3-6271-5111				

3. CFF	o quantification results, ar	nd description of CFP declration			
3.1	CFP quantification results	2,500	2,500 kg-CO2e		
	Breakdown (by life cyc	le stage, by process, by flow, etc.)			
	Raw material acquisition stage	220	kg-CO₂e		
3.2	Production stage	5.1	kg-CO₂e		
3.2	Distribution stage	24	kg-CO <sub>2</sub> e		
	Use & maintenance stage	2,300	kg-CO <sub>2</sub> e		
	Disposal & recycling stage	15	kg-CO <sub>2</sub> e		
	Value in CFP mark and d	escription of additional info.			
		<numerial value=""></numerial>	<unit for="" the="" value=""></unit>		
	Value in CFP mark	2,500kg	per unit product		
3.3	Description of additional info.	sales area. *Electric power in the use and electric-power-consumption-ra *Print volume is assumed 1,21 *In this scenario, the CO <sub>2</sub> emis CO <sub>2</sub> e at 4.0g per A4 paper.			
3.4	Remarks				
<sup>U.4</sup>	Itelliains				

to save energy during product usage.	4. Inte	erpretation of CFP quantifi	cation results
the CO2 emission during product usage.  Interpretation of CFP quantification results reduced if 2-in-1 print is applied to 607,500 sheets (50% of the estimated total print volume).  Primary data is used in the raw material consumption. Secondary data is used the parts manufacturing process which might not be reflected our own		Interpretation of CFP	CO2 emission in use and maintenance stage is the largest as 90%. It is important to save energy during product usage.  The use condition in this scenario can be different from the use condition of the user.  A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during product usage.  For example, 570kg-CO2e of the CO2 emissions (approximately 22%) can be reduced if 2-in-1 print is applied to 607,500 sheets (50% of the estimated total print volume).  Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts.

5. Cor	5. Conditions of quantification						
5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-02		
5.3	Assumptions of	Basic secondary data v.1.01 is preferentially used. Available secondary data (country v.1.04, foreign country v.1.01) is used if the items don't correspond to basic data v.1.01.					

6. Veri	6. Verification information						
6.1	Verification method	Product-by-product	6.2	CFP system certification No.	_		
6.3	Verification ID	CV-DG02-17068	6.4	Completion date of verification	July 10th, 2017		

7. Pro	7. Program information					
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	http://www.cfp-japan.jp/	
7.3	Program operator	Japan Environmental Management Association for Industry (JEMAI)	7.4	Address	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044	

7	8	Remarks	Revised on April 1st, 2021: Implemented the company name change.

For secondary data, please refer to the information on the following CFP website. http://www.cfp-japan.jp/calculate/verify/data.html