Registration Information Carbon Footprint of Products (CFP)



1. Pro	duct information		
1.1	Registration number	CR-DG02-17076-A	1.7 Product photo
1.2	Registration name	Xerox VersaLink B615 Multifunction Printer	
1.3	Model name / number	Xerox VersaLink B615 Multifunction Printer	
1.4	Main specifications of product	Print speed (Mono): 65ppm (Letter) Maximum Paper size: Legal(215.9×355.6mm) Capable of print/copy/scan/FAX, duplex printing, NFC. %print/copy/scan model is available as well. %Finisher enclosed in a red frame in the product photo is provided as an optional item. Product Size: 470.0(W)x502.8(D)x843.7(H) (mm) Product weight: 32.5kg	
1.5	CFP quantification unit	Per unit product	
1.6	CFP release date	July 27th, 2017	

2. Cor	2. Company Information				
2.1	Company name (in English)	FUJIFILM Business Innovation Corp.			
2.2	Phone number (incl. area code)	+81-3-6271-5111			

3. CFF	o quantification results, an	d description of CFP declration	
3.1	CFP quantification results	2,600	kg-CO2e
	Breakdown (by life cycl	e stage, by process, by flow, etc.)	
	Raw material acquisition stage	220	kg-CO ₂ e
3.2	Production stage	3.3	kg-CO ₂ e
5.2	Distribution stage	27	kg-CO ₂ e
	Use & maintenance stage	2,300	kg-CO ₂ e
	Disposal & recycling stage	13	kg-CO ₂ e
	Value in CFP mark and d	escription of additional info.	
		<numerial value=""></numerial>	<unit for="" the="" value=""></unit>
	Value in CFP mark	2,600kg	per unit product
3.3	Description of additional info.	of the product weight. *Calculated on the basic configura enclosed in a red frame in the pro *CO ₂ emission in the distribution s *Electric power in the use and ma power-consumption-rate in the Ur *Print volume is assumed 2,535,0 *In this scenario, the CO ₂ emissio 4.0g per A4 paper.	print/copy/scan model is 150g, which accounts for 0.5% ation, which is not equipped with the optional finisher iduct photo. stage assumes the United States as the main sales area. intenance stage is evaluated with the public electric- nited States.
3.4	Remarks		
3.4	Remarks		

4. Inte	4. Interpretation of CFP quantification results		
4.11	Interpretation of CFP quantification results	CO2 emission in use and maintenance stage is the largest as 90%. It is important to save energy during product usage. The use condition in this scenario can be different from the use condition of the user. A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during product usage. For example, 580kg-CO2e of the CO2 emissions (approximately 22%) can be reduced if 2-in-1 print is applied to 1,267,500 sheets (50% of the estimated total print volume). Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as the rough estimate according to the reason mentioned above.	

5. Cor	5. Conditions of quantification				
5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-02
5.3	Assumptions of	Basic secondary data v.1.01 is preferentially used. Available secondary data country v.1.04, foreign country v.1.01) is used if the items don't correspond to basic data v.1.01.			

6. Veri	6. Verification information					
6.1	Verification method	Product-by-product	6.2	CFP system certification No.	_	
6.3	Verification ID	CV-DG02-17076	6.4	Completion date of verification	July 21st, 2017	

7. Program information					
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	<u>http://www.cfp-japan.jp/</u>
7.3	Program operator	Japan Environmental Management Association for Industry (JEMAI)	7.4	Address	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

8 Remarks Revised on April 1st, 2021: Implemented the company name chang	8	Remarks	Revised on April 1st, 2021: Implemented the company name change.
--	---	---------	--

For secondary data, please refer to the information on the following CFP website. http://www.cfp-japan.jp/calculate/verify/data.html