Registration Information Carbon Footprint of Products (CFP)



1. Pro	1. Product information			
1.1	Registration number	CR-DG02-17083-A	1.7 Product photo	
1.2	Registration name	DocuCentre-VI C3371(For Japan)		
1.3	Model name / number DocuCentre-VI C3371		Facility of City	
1.4	Main specifications of product	Tranable of bubl/coby/scan/lax dublex bubling		
1.5	CFP quantification unit	Per unit product	300	
1.6	CFP release date	December 27th, 2017	—	

2. Company Information			
	2.1	Company name (in English)	FUJIFILM Business Innovation Corp.
ľ	2.2	Phone number (incl. area code)	+81-3-6271-5111

3. CFF	. CFP quantification results, and description of CFP decIration			
3.1	CFP quantification results	1,600	kg-CO2e	
	Breakdown (by life cycle stage, by process, by flow, etc.)			
	Raw material acquisition stage	850	kg-CO₂e	
3.2	Production stage	20	kg-CO ₂ e	
3.2	Distribution stage	27	kg-CO ₂ e	
	Use & maintenance stage	610	kg-CO ₂ e	
	Disposal & recycling stage	46	kg-CO₂e	
	Value in CFP mark and description of additional info.			
		<numerial value=""></numerial>	<unit for="" the="" value=""></unit>	
	Value in CFP mark	1,600kg	per unit product	
3.3	Description of additional info.	*Calculated by the standard Scenario for MFP (EP type). *CO ₂ emission in the distribution stage assumes Japan as the main sales area. *Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption-rate in Japan. *Print volume is assumed 740,000 sheets. *In this scenario, the CO ₂ emissions from copy papers are estimated 5,700 kg-CO ₂ e at 4.0g per A4 paper. *The CO ₂ emission of printing paper is excluded from the use and maintenance stage. Disposal & recycling stage 3% Raw material acquisition stage 55% Production stage 1% Distribution stage 2%		
3.4	Remarks			

4. Interpretation of CFP quantification results					
		important to reduce size		, ,	rargest as 55%. It is
	Interpretation of CFP quantification results	CO2 emission in use and maintenance stage is the second largest as 39%. It is important to save energy during product usage.			
4.1					
		For example, $150 \text{kg-CO}_2\text{e}$ of the CO_2 emissions (approximately 9.8%) can be reduced if 2-in-1 print is applied to 50% of the estimated total print volume.			
		Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as the rough estimate according to the reason mentioned above			
5. Conditions of quantification					
5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-02
5.3	Assumptions of secondary data used	Basic secondary data v.1.01 is preferentially used. Available secondary data (country v.1.04, foreign country v.1.01) is used if the items don't correspond to basic data v.1.01.			
6. Verification information					
6.1	Verification method	Product-by-product	6.2	CFP system certification No.	_
6.3	Verification ID	CV-DG02-17083	6.4	Completion date of verification	December 21st, 2017

6.3	Verification ID	CV-DG02-17083	6.4	Completion date of verification	December 21st, 2017
7. Program information					
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	http://www.cfp-japan.jp/
7.3	Program operator	Japan Environmental Management Association for Industry (JEMAI)	7.4	Address	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

1			
	8	Remarks	Revised on April 1st, 2021: Implemented the company name change.

For secondary data, please refer to the information on the following CFP website. http://www.cfp-japan.jp/calculate/verify/data.html