Registration Information Carbon Footprint of Products (CFP)



1. Pro	duct information			
1.1	Registration number	CR-DG02-19001-A	1.7 Product photo	
1.2	Registration name	DocuCentre-VI C4471 PFS(For Japan)		
1.3	Model name / number	DocuCentre-VI C4471 PFS(For Japan)		
1.4	Main specifications of product	Print speed (Color/Mono): 45ppm/45ppm Maximum Paper size: SRA3(320x450mm) Capable of print/copy/scan/fax, duplex printing. Product Size: 669(W)x723(D)x1141(H) (mm) Product weight: 132kg		
1.5	CFP quantification unit	Per unit product	0	
1.6	CFP release date	February 1st, 2019		

2. Co	2. Company Information					
2.1	Company name (in English)	FUJIFILM Business Innovation Corp.				
2.2	Phone number (incl. area code)	+81-3-6271-5111				

3. CFF	CFP quantification results, and description of CFP declration				
3.1	CFP quantification results	1,900	kg-CO2e		
	Breakdown (by life cycle stage, by process, by flow, etc.)				
	Raw material acquisition stage	840	kg-CO ₂ e		
3.2	Production stage	19	kg-CO ₂ e		
5.2	Distribution stage	28	kg-CO ₂ e		
	Use & maintenance stage	970	kg-CO ₂ e		
	Disposal & recycling stage	50	kg-CO ₂ e		
	Value in CFP mark and d	escription of additional info.			
		<numerial value=""></numerial>	<unit for="" the="" value=""></unit>		
	Value in CFP mark	1,900kg	per unit product		
3.3	Description of additional info.	*Calculated by the standard Scenario for MFP (EP type). *CO ₂ emission in the distribution stage assumes Japan as the main sales area. *Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption-rate in Japan. *Print volume is assumed 1,215,000 sheets. *In this scenario, the CO ₂ emissions from copy papers are estimated 9,400 kg- CO ₂ e at 4.0g per A4 paper. *The CO ₂ emission of printing paper is excluded from the use and maintenance stage. Disposal & recycling stage 3% Use & maintenance stage 51% Distribution stage			
3.4	Remarks				
.	. ternanto				

4. Inte	4. Interpretation of CFP quantification results					
4. Inte	rpretation of CFP quantifi	CO2 emission in use and maintenance stage is the largest as 51%. It is important to reduce size and weight. CO2 emission in raw material acquisition stage is the second largest as 44%. It is important to save energy during product usage. The use condition in this scenario can be different from the use condition of the				
4.1	quantification results	 user. A choice of the use condition (print mode, print conditions and so on) can reduce the CO₂ emission during product usage. For example, 240kg-CO₂e of the CO₂ emissions (approximately 13%) can be reduced if 2-in-1 print is applied to 50% of the estimated total print volume. Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as the rough estimate according to the reason mentioned above. 				

5. Cor	5. Conditions of quantification					
5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-02	
5.3	Assumptions of	Basic secondary data v.1.01 is preferentially used. Available secondary data (country v.1.04, foreign country v.1.01) is used if the items don't correspond to basic data v.1.01.				

6. Verification information						
6.1	Verification method	CFP system certification	6.2	CFP system certification No.	SCN17001	
6.3	Verification ID	FX-2018-006	6.4	Completion date of verification	October 30th, 2018	

7. Pro	7. Program information					
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	<u>http://www.cfp-japan.jp/</u>	
7.3	Program operator	Japan Environmental Management Association for Industry (JEMAI)	7.4	Address	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044	

8 Remarks Revised on April 1st, 2021: Implemented the company name change.

For secondary data, please refer to the information on the following CFP website. http://www.cfp-japan.jp/calculate/verify/data.html