Registration Information Carbon Footprint of Products (CFP)



1. Pro	1. Product information					
1.1	Registration number	CR-DG02-20003-A	1.7 Product photo			
1.2	Registration name	ApeosPort-VI C3371 PFS-2TS				
1.3	Model name / number	ApeosPort-VI C3371 PFS-2TS				
1.4	Main specifications of product	· It abable of bubl/copy/scan/lax oublex bubling				
1.5	CFP quantification unit	Per unit product	u.			
1.6	CFP release date	February 10th, 2020	(4)			

2. Cor	2. Company Information				
2.1	Company name (in English)	FUJIFILM Business Innovation Corp.			
2.2	Phone number (incl. area code)	+81-3-6271-5111			

3. CFF	CFP quantification results, and description of CFP declration					
3.1	CFP quantification results	990 kg-CO2e				
	Breakdown (by life cyc	le stage, by process, by flow, etc.)				
	Raw material acquisition stage	780	kg-CO₂e			
3.2	Production stage	20	kg-CO ₂ e			
3.2	Distribution stage	24	kg-CO₂e			
	Use & maintenance stage	130	kg-CO ₂ e			
	Disposal & recycling stage	44	kg-CO ₂ e			
	Value in CFP mark and d	lescription of additional info.				
		<numerial value=""></numerial>	<unit for="" the="" value=""></unit>			
	Value in CFP mark	990kg	per unit product			
3.3	Description of additional info.	*Electric power in the use and ma power-consumption-rate in Japan *Print volume is assumed 182,400 *In this scenario, the CO ₂ emissio 4.0g per A4 paper. *The CO ₂ emission of printing pag *Electric power in the use stage is	ation. stage assumes Japan as the main sales area. hintenance stage is evaluated with the public electric- l.			
3.4	Remarks					
-						

4. Inte	I. Interpretation of CFP quantification results					
4.1	Interpretation of CFP	CO2 emission in use and maintenance stage is the largest as 78%. It is important to reduce size and weight. The use condition in this scenario can be different from the use condition of the user. A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during product usage. For example, 32kg-CO2e of the CO2 emissions (approximately 3.2%) can be reduced if 2-in-1 print is applied to 91,200 sheets (50% of the estimated total print volume). Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as the rough estimate according to the reason mentioned above.				

ľ	5. Conditions of quantification					
	5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-02
	5.3	Assumptions of secondary data used	Basic secondary data v.1.01 is preferertially used. Available secondary data (domestic country v.1.04, foreign country v.1.0) is used if the items don't correspond to basic data v.1.01.			

ľ	6. Verification information					
I	6.1	Verification method	CFP system certification	6.2	CFP system certification No.	SCN16001
ĺ	6.3	Verification ID	FX-2019-003	6.4	Completion date of verification	January 30th, 2020

7. Program information					
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	http://www.cfp-japan.jp/
7.3	Program operator	Sustainable ManagementPromotion Organization(SuMPO)	7.4	Address	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

8	Remarks	Revised on April 1st, 2021: Implemented the company name change.
---	---------	--

For secondary data, please refer to the information on the following CFP website. http://www.cfp-japan.jp/calculate/verify/data.html