Registration Information Carbon Footprint of Products (CFP)



1. Product information				
1.1	Registration number	CR-DG02-20005-A	1.7 Product photo	
1.2	Registration name	DocuCentre-VI C5571 PFS		
1.3	Model name / number	DocuCentre-VI C5571 PFS		
1.4	Main specifications of product	Print speed (Color/Mono): 55ppm/55ppm (Letter) Maximum Paper size: SRA3(320.0×450.0mm) Capable of print/copy/scan/fax, duplex printing. Product Size: 669(W)x723(D)x1,141(H) (mm) Product weight: 132kg		
1.5	CFP quantification unit	Per unit product	[N=1	
1.6	CFP release date	February 10th, 2020	P 19	

2. Cor	2. Company Information				
2.1	Company name (in English)	FUJIFILM Business Innovation Corp.			
2.2	Phone number (incl. area code)	+81-3-6271-5111			

3.1 CFP quantification results Breakdown (by life cycle stage, by process, by flow, etc.) Raw material acquisition stage Production stage 20 kg-CO₂e Use & maintenance stage Disposal & recycling stage Value in CFP mark and description of additional info. *Numerial value> *Calculated by the standard Scenario for MFP (EP type). *Calculated by the standard Scenario for MFP (EP type). *Calculated by the standard Scenario for MFP (EP type). *Calculated on the basic configuration. *CO₂ emission in the distribution stage assumes Japan as the main sales area. *Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption-rate in Japan. *Print volume is assumed 451,200 sheets. *In this scenario, the CO₂ emissions from copy papers are estimated 3,500 kg-CO₂e at 4.0,0 per Af paper. *The CO₂ emission of printing paper is excluded from the use and maintenance stage. *Electric power in the use stage is evaluated based on TEC value which is measured in acordance with International ENERGY STAR Program version 3.0. Use & maintenance stage Disposal & recycling stage Aw material acquisition stage Froduction stage Disposal & recycling stage Aw material acquisition stage Froduction stage Production stage	3. CFF	. CFP quantification results, and description of CFP declration					
Raw material acquisition stage Production stage Production stage 20 kg-CO ₂ e Distribution stage 26 kg-CO ₂ e		CFP quantification	i i	kg-CO2e			
3.2 Production stage 20 kg-CO ₂ e Distribution stage 26 kg-CO ₂ e Use & maintenance stage 310 kg-CO ₂ e Disposal & recycling stage 50 kg-CO ₂ e Value in CFP mark and description of additional info. Value in CFP mark 1,200kg Per unit product *Calculated by the standard Scenario for MFP (EP type). *Calculated on the basic configuration. *Co ₂ emission in the distribution stage assumes Japan as the main sales area. *Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption-rate in Japan. *Print volume is assumed 451,200 sheets. *In this scenario, the CO ₂ emissions from copy papers are estimated 3,500 kg-CO ₂ e at 4.0g per A4 paper. *The CO ₂ emission of printing paper is excluded from the use and maintenance stage. *Electric power in the use stage is evaluated based on TEC value which is measured in acordance with International ENERGY STAR Program version 3.0. Description of additional info. Use & maintenance stage Disposal & recycling stage 4% Production stage Production stage Production stage 2% Production stage		Breakdown (by life cyc	le stage, by process, by flow, etc.)				
Distribution stage 26 kg-CO2e		· ·	830	kg-CO₂e			
Distribution stage Use & maintenance stage Disposal & recycling stage Value in CFP mark and description of additional info. Value in CFP mark and description of additional info. Value in CFP mark 1,200kg Per unit product *Calculated by the standard Scenario for MFP (EP type). *Calculated on the basic configuration. *CO2 emission in the distribution stage assumes Japan as the main sales area. *Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption-rate in Japan. *Print volume is assumed 451,200 sheets. *In this scenario, the CO2 emissions from copy papers are estimated 3,500 kg-CO2e at 4.0g per A4 paper. *The CO2 emission of printing paper is excluded from the use and maintenance stage. *Electric power in the use stage is evaluated based on TEC value which is measured in acordance with International ENERGY STAR Program version 3.0. Description of additional info. Use & maintenance stage Disposal & recycling stage 4% Production stage Production stage Production stage Production stage Production stage **Raw material acquisition stage 67% **Raw material acquisition stage **Raw material acquisition stage **Raw material acquisition stage **Telectric power in the use stage is evaluated based on TEC value which is measured in accordance with International ENERGY STAR Program version 3.0. **Disposal & recycling stage **Amaterial acquisition stage **Production stage **Production stage **Production stage **Production stage **Production stage **Production stage **Telectric power in the use stage is evaluated based on TEC value which is measured in accordance with International ENERGY STAR Program version 3.0. **Production stage** **Productio	2.0	Production stage	20	kg-CO ₂ e			
Disposal & recycling stage Value in CFP mark and description of additional info. Value in CFP mark 1,200kg Per unit product *Calculated by the standard Scenario for MFP (EP type). *Calculated on the basic configuration. *CO ₂ emission in the distribution stage assumes Japan as the main sales area. *Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption-rate in Japan. *Print volume is assumed 451,200 sheets. *In this scenario, the CO ₂ emissions from copy papers are estimated 3,500 kg-CO ₂ e at 4.0g per A4 paper. *The CO ₂ emission of printing paper is excluded from the use and maintenance stage. *Electric power in the use stage is evaluated based on TEC value which is measured in acordance with International ENERGY STAR Program version 3.0. Use & maintenance stage Disposal & recycling stage 4% Distribution stage Production stage Production stage	3.2	Distribution stage	26	kg-CO₂e			
Value in CFP mark and description of additional info. Value in CFP mark		Use & maintenance stage	310	kg-CO₂e			
Value in CFP mark 1,200kg *Calculated by the standard Scenario for MFP (EP type). *Calculated on the basic configuration. *CO ₂ emission in the distribution stage assumes Japan as the main sales area. *Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption-rate in Japan. *Print volume is assumed 451,200 sheets. *In this scenario, the CO ₂ emissions from copy papers are estimated 3,500 kg-CO ₂ e at 4.0g per A4 paper. *The CO ₂ emission of printing paper is excluded from the use and maintenance stage. *Electric power in the use stage is evaluated based on TEC value which is measured in acordance with International ENERGY STAR Program version 3.0. Use & maintenance stage Disposal & recycling stage 4% Production stage Production stage 2% Production stage		. , ,		kg-CO ₂ e			
*Calculated by the standard Scenario for MFP (EP type). *Calculated on the basic configuration. *CO ₂ emission in the distribution stage assumes Japan as the main sales area. *Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption-rate in Japan. *Print volume is assumed 451,200 sheets. *In this scenario, the CO ₂ emissions from copy papers are estimated 3,500 kg-CO ₂ e at 4.0g per A4 paper. *The CO ₂ emission of printing paper is excluded from the use and maintenance stage. *Electric power in the use stage is evaluated based on TEC value which is measured in acordance with International ENERGY STAR Program version 3.0. Use & maintenance stage Disposal & recycling stage 4% Distribution stage 2% Production stage 2% Production stage		Value in CFP mark and d					
*Calculated by the standard Scenario for MFP (EP type). *Calculated on the basic configuration. *CO ₂ emission in the distribution stage assumes Japan as the main sales area. *Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption-rate in Japan. *Print volume is assumed 451,200 sheets. *In this scenario, the CO ₂ emissions from copy papers are estimated 3,500 kg-CO ₂ e at 4.0g per A4 paper. *The CO ₂ emission of printing paper is excluded from the use and maintenance stage. *Electric power in the use stage is evaluated based on TEC value which is measured in acordance with International ENERGY STAR Program version 3.0. Use & maintenance stage Disposal & recycling stage 4% Production stage Production stage 2% Production stage			<numerial value=""></numerial>	<unit for="" the="" value=""></unit>			
*Calculated on the basic configuration. *CO ₂ emission in the distribution stage assumes Japan as the main sales area. *Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption-rate in Japan. *Print volume is assumed 451,200 sheets. *In this scenario, the CO ₂ emissions from copy papers are estimated 3,500 kg-CO ₂ e at 4.0g per A4 paper. *The CO ₂ emission of printing paper is excluded from the use and maintenance stage. *Electric power in the use stage is evaluated based on TEC value which is measured in acordance with International ENERGY STAR Program version 3.0. Use & maintenance stage Disposal & recycling stage 4% Distribution stage Production stage 2% Production stage		Value in CFP mark	1,200kg	per unit product			
2% Froduction stage 2%	3.3	•	*CO ₂ emission in the distribution s *Electric power in the use and mapower-consumption-rate in Japan *Print volume is assumed 451,20 *In this scenario, the CO ₂ emission 4.0g per A4 paper. *The CO ₂ emission of printing paper in the use stage is accordance with International ENE	stage assumes Japan as the main sales area. aintenance stage is evaluated with the public electric- b. 0 sheets. ons from copy papers are estimated 3,500 kg-CO ₂ e at oper is excluded from the use and maintenance stage. It is evaluated based on TEC value which is measured in ERGY STAR Program version 3.0. Disposal & recycling stage			
3.4 Remarks			2% Production stage	Raw material acquisition stage			
	3.4	Remarks					

4	4. Interpretation of CFP quantification results					
	. Inte	Interpretation of CFP	CO2 emission in use and maintenance stage is the largest as 67%. It is important to reduce size and weight. The use condition in this scenario can be different from the use condition of the user. A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during product usage. For example, 76kg-CO2e of the CO2 emissions (approximately 6.2%) can be reduced if 2-in-1 print is applied to 225,600 sheets (50% of the estimated total print volume). Primary data is used in the raw material consumption. Secondary data is used in			
			Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as the rough estimate according to the reason mentioned above.			

ľ	5. Conditions of quantification					
	5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-02
	5.3	Assumptions of secondary data used	Basic secondary data v.1. (domestic country v.1.04、 to basic data v.1.01.		•	allable secondary data d if the items don't correspond

6. Veri	6. Verification information				
6.1	Verification method	CFP system certification	6.2	CFP system certification No.	SCN16001
6.3	Verification ID	FX-2019-001	6.4	Completion date of verification	January 24th, 2020

7. Pro	7. Program information				
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	http://www.cfp-japan.jp/
7.3	Program operator	Sustainable ManagementPromotion Organization(SuMPO)	7.4	Δαατρές	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

8	Remarks	Revised on April 1st, 2021: Implemented the company name change.

For secondary data, please refer to the information on the following CFP website. http://www.cfp-japan.jp/calculate/verify/data.html