Registration Information Carbon Footprint of Products (CFP)



1. Product information							
1.1	Registration number	CR-DG02-20008-A	1.7 Product photo				
1.2	Registration name	DocuCentre-VI C7771 PFS					
1.3	Model name / number	DocuCentre-VI C7771 PFS					
1.4	Main specifications of product	Print speed: Color 70ppm/Monochrome 70ppm Maximum Paper size: SRA3(320x450mm) Capable of print/copy/scan/FAX, duplex printing. Product Size: 620(W)x793(D)x1,169(H) (mm) Product weight: 155kg					
1.5	CFP quantification unit	Per unit product					
1.6	CFP release date	March 18th, 2020					

2. Cor	2. Company Information				
2.1	Company name (in English)	FUJIFILM Business Innovation Corp.			
2.2	Phone number (incl. area code)	+81-3-6271-5111			

3 CEP	Quantification results and	d description of CFP declration		
3.1	CFP quantification results	1,700	kg-CO2e	
	Breakdown (by life cycle stage, by process, by flow, etc.)			
	Raw material acquisition stage	950	kg-CO ₂ e	
2.2	Production stage	19	kg-CO ₂ e	
3.2	Distribution stage	31	kg-CO ₂ e	
	Use & maintenance stage	600	kg-CO ₂ e	
	Disposal & recycling stage	55	kg-CO ₂ e	
	Value in CFP mark and de	escription of additional info.		
		<numerial value=""></numerial>	<unit for="" the="" value=""></unit>	
	Value in CFP mark	1,700kg	per unit product	
3.3	Description of additional info.	*Electric power in the use and r power-consumption-rate in Jap *Print volume is assumed 730,0 *In this scenario, the CO ₂ emiss 4.0g per A4 paper. *The CO ₂ emission of printing p *Electric power in the use stage	uration. In stage assumes Japan as the main sales area. maintenance stage is evaluated with the public electric- an. 200 sheets. Sions from copy papers are estimated 5,600 kg-CO ₂ e at paper is excluded from the use and maintenance stage. The is evaluated based on TEC value which is measured in NERGY STAR Program version 3.0. The material acquisition stage 58%	
3.4	Remarks			
J.4	remarks			

4. Inter	4. Interpretation of CFP quantification results						
4.1	Interpretation of CEP	CO2 emission in use and maintenance stage is the largest as 58%. It is important to save energy during product usage. The use condition in this scenario can be different from the use condition of the user. A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during product usage. For example, 150kg-CO2e of the CO2 emissions (approximately 9%) can be reduced if 2-in-1 print is applied to 50% of the estimated total print volume. Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as the rough estimate according to the reason mentioned above.					

5. Cor	onditions of quantification				
5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-02
5.3	Assumptions of	Basic secondary data v.1.01 is preferertially used. Available secondary data domestic country v.1.04, foreign country v.1.0) is used if the items don't correspond to basic data v.1.01.			

	6. Verification information					
	6.1	Verification method	CFP system certification	6.2	CFP system certification No.	SCN16001
ĺ	6.3	Verification ID	FX-2019-004	6.4	Completion date of verification	March 10th, 2020

7. Pro	. Program information				
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	<u>http://www.cfp-japan.jp/</u>
7.3	Program operator	Sustainable ManagementPromotion Organization(SuMPO)	7.4	Address	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

	8	Remarks	Revised on April 1st, 2021: Implemented the company name change.
--	---	---------	--

For secondary data, please refer to the information on the following CFP website. http://www.cfp-japan.jp/calculate/verify/data.html