Registration Information Carbon Footprint of Products (CFP)



1. Prod	1. Product information					
1.1	Registration number	CR-DG02-20009-A	1.7 Product photo			
1.2	Registration name	DocuCentre-VI C3371 P				
1.3	Model name / number	DocuCentre-VI C3371 P	1 1 1			
1.4	Main specifications of product	Print speed: Color 35ppm/Monochrome 35ppm Maximum Paper size: SRA3(320x450mm) Capable of print/copy, duplex printing. Product Size: 669(W)x723(D)x1,040(H) (mm) Product weight: 122kg	n			
1.5	CFP quantification unit	Per unit product				
1.6	CFP release date	February 28th, 2020				

2	2. Company Information				
	2.1	Company name (in English)	FUJIFILM Business Innovation Corp.		
ſ	2.2	Phone number (incl. area code)	+81-3-6271-5111		

3. CFF	CFP quantification results, and description of CFP declration				
3.1	CFP quantification results	1,400 kg-CO2e			
	Breakdown (by life cycl	e stage, by process, by flow, etc.)			
	Raw material acquisition stage	780	kg-CO ₂ e		
3.2	Production stage	20	kg-CO ₂ e		
3.2	Distribution stage	27	kg-CO₂e		
	Use & maintenance stage	570	kg-CO₂e		
	Disposal & recycling stage	48	kg-CO₂e		
	Value in CFP mark and d	escription of additional info.			
		<numerial value=""></numerial>	<unit for="" the="" value=""></unit>		
	Value in CFP mark	1,400kg	per unit product		
3.3	Description of additional info.	*Electric power in the use and r power-consumption-rate in Jap *Print volume is assumed 730,0 *In this scenario, the CO ₂ emiss 4.0g per A4 paper. *The CO ₂ emission of printing p *Electric power in the use stage	uration. In stage assumes Japan as the main sales area. The maintenance stage is evaluated with the public electrican.		
3.4	Remarks				
J. T	Remains				

4. Inter	4. Interpretation of CFP quantification results					
4.1	Interpretation of CED	CO2 emission in use and maintenance stage is the largest as 54%. It is important to save energy during product usage. The use condition in this scenario can be different from the use condition of the user. A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during product usage. For example, 140kg-CO2e of the CO2 emissions (approximately 10%) can be reduced if 2-in-1 print is applied to 50% of the estimated total print volume. Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as the rough estimate according to the reason mentioned above.				

5. Con	5. Conditions of quantification				
5.1	Name of approved CFP-PCR	maging input and/or output equipment 5.2 Approved CFP-PCR ID PA-DG-02			
5.3	Assumptions of	Basic secondary data v.1.01 is preferentially used. Available secondary data (domestic country v.1.04, foreign country v.1.0) is used if the items don't correspond to basic data v.1.01.			

6. Veri	6. Verification information					
6.1	Verification method	CFP system certification	6.2	CFP system certification No.	SCN16001	
6.3	Verification ID	FX-2019-008	6.4	Completion date of verification	January 30th, 2020	

7. Prog	7. Program information				
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	http://www.cfp-japan.jp/
7.3	Program operator	Sustainable ManagementPromotion Organization(SuMPO)	7.4	Address	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

	8	Remarks	Revised on April 1st, 2021: Implemented the company name change.
--	---	---------	--

For secondary data, please refer to the information on the following CFP website. http://www.cfp-japan.jp/calculate/verify/data.html