Registration Information Carbon Footprint of Products (CFP)



1. Product information						
1.1	Registration number	CR-DG02-20010-A	1.7 Product photo			
1.2	Registration name	DocuCentre-VI C2271 P				
1.3	Model name / number					
1.4	Main specifications of product	Print speed: Color 25ppm/Monochrome 25ppm Maximum Paper size: SRA3(320x450mm) Capable of print/copy, duplex printing. Product Size: 669(W)x723(D)x1,040(H) (mm) Product weight: 122kg	91			
1.5	CFP quantification unit	Per unit product				
1.6	CFP release date	February 28th, 2020				

2. Coi	2. Company Information				
2.1	Company name (in English)	FUJIFILM Business Innovation Corp.			
2.2	Phone number (incl. area code)	+81-3-6271-5111			

3.1	CFP quantification results	1 100	
-	Due alestaria (lassilita assala	1,100 kg-CO2e	
1	Breakdown (by life cycle	e stage, by process, by flow, etc.)	
	Raw material acquisition stage	780	kg-CO ₂ e
3.2	Production stage	20	kg-CO ₂ e
3.2	Distribution stage	27	kg-CO ₂ e
ι	Use & maintenance stage	270	kg-CO ₂ e
	Disposal & recycling stage	48	kg-CO ₂ e
Va	alue in CFP mark and de	escription of additional info.	
		<numerial value=""></numerial>	<unit for="" the="" value=""></unit>
	Value in CFP mark	1,100kg	per unit product
3.3	Description of additional info.	*Calculated by the standard Scenario for MFP (EP type). *Calculated on the basic configuration. *CO ₂ emission in the distribution stage assumes Japan as the main sales area. *Electric power in the use and maintenance stage is evaluated with the public elect power-consumption-rate in Japan. *Print volume is assumed 360,000 sheets. *In this scenario, the CO ₂ emissions from copy papers are estimated 2,800 kg-CO ₂ 4.0g per A4 paper. *The CO ₂ emission of printing paper is excluded from the use and maintenance sta *Electric power in the use stage is evaluated based on TEC value which is measur acordance with International ENERGY STAR Program version 2.0. Disposal & recycling stage 4% Use & maintenance stage 24% Distribution stage 2%	
3.4	Remarks		

4. Inter	4. Interpretation of CFP quantification results					
4.11	Interpretation of CFP quantification results	CO2 emission in use and maintenance stage is the largest as 68%. It is important to save energy during product usage. The use condition in this scenario can be different from the use condition of the user. A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during product usage. For example, 67kg-CO2e of the CO2 emissions (approximately 6%) can be reduced if 2-in-1 print is applied to 50% of the estimated total print volume. Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as the rough estimate according to the reason mentioned above.				

5. Cor	. Conditions of quantification				
5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-02
5.3	Assumptions of	Basic secondary data v.1.01 is preferentially used. Available secondary data (domestic country v.1.04, foreign country v.1.0) is used if the items don't correspond to basic data v.1.01.			

	6. Verification information					
	6.1	Verification method	CFP system certification	6.2	CFP system certification No.	SCN16001
ĺ	6.3	Verification ID	FX-2019-009	6.4	Completion date of verification	January 30th, 2020

7. Program information					
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	<u>http://www.cfp-japan.jp/</u>
7.3	Program operator	Sustainable ManagementPromotion Organization(SuMPO)	7.4	Address	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

8	Remarks	Revised on April 1st, 2021: Implemented the company name change.

For secondary data, please refer to the information on the following CFP website. http://www.cfp-japan.jp/calculate/verify/data.html