## Registration Information Carbon Footprint of Products (CFP)



1. Pro	1. Product information					
1.1	Registration number	CR-DG02-20012-A	1.7 Product photo			
1.2	Registration name	Xerox PrimeLink B9110 Copier/Printer				
1.3	Model name / number	Xerox PrimeLink B9110 Copier/Printer				
1.4	4 Main specifications of product Print speed (Mono): 110ppm (Letter) Maximum Paper size: 330mmx488mm Capable of print/copy/scan, duplex printing. Product Size: 2,339(W)x913(D)x1,477(H) (mm) Product weight: 392kg					
1.5	CFP quantification unit	Per unit product				
1.6	CFP release date	February 17th, 2020				

2. Cor	2. Company Information				
2.1	Company name (in English)	FUJIFILM Business Innovation Corp.			
2.2	Phone number (incl. area code)	+81-3-6271-5111			

3. CFF	CFP quantification results, and description of CFP declration					
3.1	CFP quantification results	11,000	kg-CO2e			
	Breakdown (by life cyc	le stage, by process, by flow, etc.	)			
	Raw material acquisition stage	1,900	kg-CO <sub>2</sub> e			
3.2	Production stage	18	kg-CO <sub>2</sub> e			
3.2	Distribution stage	430	kg-CO <sub>2</sub> e			
	Use & maintenance stage	8,500	kg-CO <sub>2</sub> e			
	Disposal & recycling stage	120	kg-CO <sub>2</sub> e			
	Value in CFP mark and c	lescription of additional info.				
		<numerial value=""></numerial>	<unit for="" the="" value=""></unit>			
	Value in CFP mark	11,000kg	per unit product			
3.3	Description of additional info.	*Electric power in the use and mapower-consumption-rate in the U *Print volume is assumed 7,260, *In this scenario, the CO <sub>2</sub> emission 4.0g per A4 paper. *The CO <sub>2</sub> emission of printing pa *Electric power in the use stage in	stage assumes the United States as the main sales area. aintenance stage is evaluated with the public electric- Inited States.			
		Disposal & recycling stage 1% Use & maintenance stage 78%	Raw material acquisition stage 17% Production stage 0.2% Distribution stage 4%			
3.4	Remarks					

4. Inte	4. Interpretation of CFP quantification results						
		CO2 emission in use and maintenance stage is the largest as 78%. It is important to save energy during product usage.					
4.1		The use condition in this scenario can be different from the use condition of the user. A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during product usage. For example, 2,100kg-CO2e of the CO2 emissions (approximately 19%) can be reduced if 2-in-1 print is applied to 50% of the estimated total print volume. Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as the rough estimate according to the reason mentioned above.					

5. Cor	5. Conditions of quantification				
5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-02
5.3	Assumptions of	Basic secondary data v.1.01 is preferertially used. Available secondary data (domestic country v.1.04, foreign country v.1.0) is used if the items don't correspond to basic data v.1.01.			

6	6. Verification information					
	6.1	Verification method	CFP system certification	6.2	CFP system certification No.	SCN16001
ſ	6.3	Verification ID	FX-2020-002	6.4	Completion date of verification	February 7th, 2020

7. Program information					
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	<u>http://www.cfp-japan.jp/</u>
7.3	Program operator	Sustainable ManagementPromotion Organization(SuMPO)	7.4	Address	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

8	Remarks	Revised on April 1st, 2021: Implemented the company name change.
---	---------	--

For secondary data, please refer to the information on the following CFP website. http://www.cfp-japan.jp/calculate/verify/data.html