## Registration Information Carbon Footprint of Products (CFP)



1. Pro	1. Product information				
1.1	Registration number	CR-DG02-20014-A	1.7 Product photo		
1.2	Registration name	Xerox PrimeLink B9136 Copier/Printer			
1.3	Model name / number	Xerox PrimeLink B9136 Copier/Printer			
1.4	Main specifications of product	Print speed (Mono): 136ppm (Letter) Maximum Paper size: 330×488mm) Capable of print/copy/scan, duplex printing. Product Size: 2,339(W)x913(D)x1,477(H) (mm) Product weight: 392kg			
1.5	CFP quantification unit	Per unit product			
1.6	CFP release date	February 17th, 2020			

2. Cor	2. Company Information				
2.1	Company name (in English)	FUJIFILM Business Innovation Corp.			
2.2	Phone number (incl. area code)	+81-3-6271-5111			

*Electric power in the use and maintenance stage is evaluated with the public electric power-consumption-rate in the United States.  *Print volume is assumed 11,090,000 sheets.  *In this scenario, the CO <sub>2</sub> emissions from copy papers are estimated 86,000 kg-CO <sub>2</sub> 4.0g per A4 paper.  *The CO <sub>2</sub> emission of printing paper is excluded from the use and maintenance stage *Electric power in the use stage is evaluated based on TEC value which is measured accordance with International ENERGY STAR Program version 3.0.  Disposal & recycling stage  15%  Production stage 0.1%  Distribution stage 81%	3. CFF	. CFP quantification results, and description of CFP declration					
Raw material acquisition stage Production stage 18 kg-CO₂e Distribution stage 430 kg-CO₂e Use & maintenance stage 11,000 kg-CO₂e Disposal & recycling stage 120 kg-CO₂e Value in CFP mark and description of additional info.  Value in CFP mark  *Calculated by the standard Scenario for MFP (EP type).  *Calculated on the basic configuration.  *CO₂ emission in the distribution stage assumes the United States as the main sales *Electric power in the use and maintenance stage is evaluated with the public electric power-consumption-rate in the United States.  *Print volume is assumed 11,090,000 sheets.  *In this scenario, the CO₂ emissions from copy papers are estimated 86,000 kg-CO₂ 4.0g per A4 paper.  *The CO₂ emission of printing paper is excluded from the use and maintenance stage *Electric power in the use stage is evaluated based on TEC value which is measured acordance with International ENERGY STAR Program version 3.0.  Description of additional info.  Disposal & recycling stage    Co₂ emission of printing paper is excluded from the use and maintenance stage telectric power in the use stage is evaluated based on TEC value which is measured acordance with International ENERGY STAR Program version 3.0.    Co₂ emission of printing paper is excluded from the use and maintenance stage telectric power in the use stage is evaluated based on TEC value which is measured acordance with International ENERGY STAR Program version 3.0.    Co₂ emission of printing paper is excluded from the use and maintenance stage telectric power in the use stage is evaluated based on TEC value which is measured acordance with International ENERGY STAR Program version 3.0.	3.1		13,000	kg-CO2e			
Stage   Production stage   18   kg-CO2e			e stage, by process, by flow, etc.)				
Distribution stage			2,000	kg-CO₂e			
Distribution stage  Use & maintenance stage  Disposal & recycling stage  120 kg-CO <sub>2</sub> e  Value in CFP mark and description of additional info.  Value in CFP mark  13,000kg  Per unit product  *Calculated by the standard Scenario for MFP (EP type).  *Calculated on the basic configuration.  *CO <sub>2</sub> emission in the distribution stage assumes the United States as the main sales *Electric power in the use and maintenance stage is evaluated with the public electric power-consumption-rate in the United States.  *Print volume is assumed 11,090,000 sheets.  *In this scenario, the CO <sub>2</sub> emissions from copy papers are estimated 86,000 kg-CO <sub>2</sub> 4.0g per A4 paper.  *The CO <sub>2</sub> emission of printing paper is excluded from the use and maintenance stage *Electric power in the use stage is evaluated based on TEC value which is measured acordance with International ENERGY STAR Program version 3.0.  Description of additional info.  Disposal & recycling stage  15%  Production stage 0.1%  Distribution stage 0.1%  Distribution stage 0.1%	2.0	Production stage	18	kg-CO₂e			
Disposal & recycling stage  Value in CFP mark and description of additional info.  Value in CFP mark  13,000kg  **Calculated by the standard Scenario for MFP (EP type).  **Calculated on the basic configuration.  **CO2 emission in the distribution stage assumes the United States as the main sales  *Electric power in the use and maintenance stage is evaluated with the public electric power-consumption-rate in the United States.  *Print volume is assumed 11,090,000 sheets.  *In this scenario, the CO2 emissions from copy papers are estimated 86,000 kg-CO2 degrees as the stage is evaluated from the use and maintenance stage is evaluated based on TEC value which is measured accordance with International ENERGY STAR Program version 3.0.  Description of additional info.  Disposal & recycling stage  1%  Production stage 0.1%  Distribution stage 0.1%  Distribution stage 3%	3.2	Distribution stage	430	kg-CO <sub>2</sub> e			
Value in CFP mark and description of additional info.    Value in CFP mark   Summerial value   Summerial value   Per unit product		Use & maintenance stage	11,000	kg-CO₂e			
Value in CFP mark  13,000kg  per unit product  *Calculated by the standard Scenario for MFP (EP type).  *Calculated on the basic configuration.  *CO₂ emission in the distribution stage assumes the United States as the main sales  *Electric power in the use and maintenance stage is evaluated with the public electric power-consumption-rate in the United States.  *Print volume is assumed 11,090,000 sheets.  *In this scenario, the CO₂ emissions from copy papers are estimated 86,000 kg-CO₂  4.0g per A4 paper.  *The CO₂ emission of printing paper is excluded from the use and maintenance stage  *Electric power in the use stage is evaluated based on TEC value which is measured acordance with International ENERGY STAR Program version 3.0.  Disposal & recycling stage    Raw material acquisition stage   15%		. , ,		kg-CO <sub>2</sub> e			
*Calculated by the standard Scenario for MFP (EP type). *Calculated on the basic configuration. *CO <sub>2</sub> emission in the distribution stage assumes the United States as the main sales *Electric power in the use and maintenance stage is evaluated with the public electric power-consumption-rate in the United States. *Print volume is assumed 11,090,000 sheets. *In this scenario, the CO <sub>2</sub> emissions from copy papers are estimated 86,000 kg-CO <sub>2</sub> 4.0g per A4 paper. *The CO <sub>2</sub> emission of printing paper is excluded from the use and maintenance stage *Electric power in the use stage is evaluated based on TEC value which is measured accordance with International ENERGY STAR Program version 3.0.  Disposal & recycling stage  The Co <sub>2</sub> emission of printing paper is excluded from the use and maintenance stage *Electric power in the use stage is evaluated based on TEC value which is measured accordance with International ENERGY STAR Program version 3.0.  Disposal & recycling stage  The Co <sub>2</sub> emission of printing paper is excluded from the use and maintenance stage *Electric power in the use stage is evaluated based on TEC value which is measured accordance with International ENERGY STAR Program version 3.0.  Disposal & recycling stage  The Co <sub>2</sub> emission of printing paper is excluded from the use and maintenance stage *Electric power in the use stage is evaluated based on TEC value which is measured accordance with International ENERGY STAR Program version 3.0.  Disposal & recycling stage  The Co <sub>2</sub> emission of printing paper is excluded from the use and maintenance stage *Electric power in the United States.  The Co <sub>2</sub> emission of printing paper is excluded from the use and maintenance stage *Electric power in the United States.  The Co <sub>2</sub> emission of printing paper is excluded from the use and maintenance stage *Electric power in the United States.  The Co <sub>2</sub> emission of printing		Value in CFP mark and d	escription of additional info.				
*Calculated by the standard Scenario for MFP (EP type).  *Calculated on the basic configuration.  *CO <sub>2</sub> emission in the distribution stage assumes the United States as the main sales  *Electric power in the use and maintenance stage is evaluated with the public electric power-consumption-rate in the United States.  *Print volume is assumed 11,090,000 sheets.  *In this scenario, the CO <sub>2</sub> emissions from copy papers are estimated 86,000 kg-CO <sub>2</sub> 4.0g per A4 paper.  *The CO <sub>2</sub> emission of printing paper is excluded from the use and maintenance stage  *Electric power in the use stage is evaluated based on TEC value which is measured accordance with International ENERGY STAR Program version 3.0.  Disposal & recycling stage  15%  Production stage 0.1%  Distribution stage 3%  Distribution stage 3%			<numerial value=""></numerial>	<unit for="" the="" value=""></unit>			
*Calculated on the basic configuration.  *CO <sub>2</sub> emission in the distribution stage assumes the United States as the main sales *Electric power in the use and maintenance stage is evaluated with the public electri power-consumption-rate in the United States.  *Print volume is assumed 11,090,000 sheets.  *In this scenario, the CO <sub>2</sub> emissions from copy papers are estimated 86,000 kg-CO <sub>2</sub> 4.0g per A4 paper.  *The CO <sub>2</sub> emission of printing paper is excluded from the use and maintenance stage *Electric power in the use stage is evaluated based on TEC value which is measured acordance with International ENERGY STAR Program version 3.0.  Disposal & recycling stage    Raw material acquisition stage 15%		Value in CFP mark	13,000kg	per unit product			
Use & maintenance stage 3%	3.3	•	*Calculated on the basic configuration.  *CO <sub>2</sub> emission in the distribution stage assumes the United States as the main sales area.  *Electric power in the use and maintenance stage is evaluated with the public electric- power-consumption-rate in the United States.  *Print volume is assumed 11,090,000 sheets.  *In this scenario, the CO <sub>2</sub> emissions from copy papers are estimated 86,000 kg-CO <sub>2</sub> e at 4.0g per A4 paper.  *The CO <sub>2</sub> emission of printing paper is excluded from the use and maintenance stage.  *Electric power in the use stage is evaluated based on TEC value which is measured in acordance with International ENERGY STAR Program version 3.0.  Disposal & recycling stage  1%  Raw material acquisition stage  Production stage				
3.4 Remarks	3.4	Remarks					

4. Interpretation of CFP quantification results					
4. Inte	Interpretation of CFP	CO2 emission in use and maintenance stage is the largest as 81%. It is important to save energy during product usage.  The use condition in this scenario can be different from the use condition of the user.  A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during product usage.  For example, 2,700kg-CO2e of the CO2 emissions (approximately 20%) can be reduced if 2-in-1 print is applied to 5,548,000 sheets (50% of the estimated total print volume).			
		Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as the rough estimate according to the reason mentioned above.			

5. Cor	5. Conditions of quantification				
5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-02
5.3	Assumptions of	Basic secondary data v.1.01 is preferertially used. Available secondary data (domestic country v.1.04, foreign country v.1.0) is used if the items don't correspond to basic data v.1.01.			

6. Ver	6. Verification information					
6.1	Verification method	CFP system certification	6.2	CFP system certification No.	SCN16001	
6.3	Verification ID	FX-2020-004	6.4	Completion date of verification	February 7th, 2020	

7. Pro	7. Program information				
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	http://www.cfp-japan.jp/
7.3	Program operator	Sustainable ManagementPromotion Organization(SuMPO)	7.4		2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

8	Remarks	Revised on April 1st, 2021: Implemented the company name change.
---	---------	--

For secondary data, please refer to the information on the following CFP website. http://www.cfp-japan.jp/calculate/verify/data.html