Registration Information Carbon Footprint of Products (CFP)



1. Pro	duct information		
1.1	Registration number	CR-DG01-16062	1.7 Product photo
1.2	Registration name	DocuCentre-V C2276 PFS	
1.3	Model name / number	DocuCentre-V C2276 PFS	
1.4	Main specifications of product	Print speed (Color/Mono): 25ppm/25ppm Paper size: SRA3(320x450mm) maximum Capable of duplex printing, facsimile and scanning Product Size: 640(W)x699(D)x1128(H) (mm) Product weight: 129kg	
1.5	CFP quantification unit	Per unit product	
1.6	CFP release date	2016/10/28	P) (P)

2. Company Information			
2.1	Company name (in English)	Fuji Xerox Co., Ltd.	
2.2	Phone number (incl. area code)	+81-3-6271-5111	

3. CFF	o quantification results, ar	nd description of CFP declration	
3.1	CFP quantification results	1,300	kg-CO2e
	Breakdown (by life cyc	le stage, by process, by flow, etc.)	
	Raw material acquisition stage	850	kg-CO₂e
3.2	Production stage	17	kg-CO₂e
3.2	Distribution stage	27	kg-CO₂e
	Use & maintenance stage	370	kg-CO₂e
	Disposal & recycling stage	47	kg-CO₂e
	Value in CFP mark and o	description of additional info.	
		<numerial value=""></numerial>	<unit for="" the="" value=""></unit>
	Value in CFP mark	1,300 kg	per unit product
3.3	Description of additional info.	*Calculated by the standard Scer *CO ₂ emission in the distribution assumes Japan as the main sale *Electric power in the use and maintenance stage is evaluated of the public electric-power-consum -rate in Japan. *The CO ₂ emission due to printin paper is excluded from the use and maintenance stage. *Print volume is assumed 375,00 sheets.	stage s area. with ^{28%} g ^{65%} BRaw material acquisition stage Distribution stage Distribution stage
3.4	Remarks	*Print volume: 375,000 sheets *In this scenario, the CO ₂ emission g per A4 paper.	ons from copy papers are estimated 2,900 kg-CO ₂ e at 4.0

1 Inter	matation of CED quantifi	action requite
4. Intel	rpretation of CFP quantifi	
I I		CO2 emission in raw material acquisition stage is the largest as 65%. It is
I I		important to reduce size and weight.
I I		
I I		
		CO2 emission in use and maintenance stage is the second largest as 28%. It is
		important to save energy during product usage.
		The use condition in this scenario can be different from the use condition of the
I I		user.
	Interpretation of CFP	A choice of the use condition (print mode, print conditions and so on) can reduce
4.1	quantification results	the CO2 emission during product usage.
	quantineation results	
I I		For example, 91.25kg-CO2e of the CO2 emissions (approximately 7%) can be
		reduced if 2-in-1 print is applied to 187,500sheets (50% of print volume).
		Primary data is used in the raw material consumption. Secondary data is used in
I I		
		the parts manufacturing process which might not be reflected our own
		circumstances because it is difficult to collect the data for thousands of the parts.
		Please understand this result as the rough estimate according to the reason
		с с с
		mentioned above.

5. Cor	5. Conditions of quantification				
5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-01
5.3	Assumptions of	Basic secondary data v.1.01 is preferentially used. Available secondary data (country v.1.04, foreign country v.1.01) is used if the items don't correspond to basic data v.1.01.		2	

6. Veri	fication information				
6.1	Verification method	Product-by-product	6.2	CFP system certification No.	_
6.3	Verification ID	CV-DG01-16062	6.4	Completion date of verification	2016年10月20日

7. Progr	ram information				
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	http://www.cfp-japan.jp/
7.3	Program operator	Japan Environmental Management Association for Industry (JEMAI)	7.4	Address	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

8 Remarks -

For secondary data, please refer to the information on the following CFP website. http://www.cfp-japan.jp/calculate/verify/data.html