



Registration Information Carbon Footprint of Products (CFP)



1. Product information			
1.1	Registration number	CR-DG01-16047	1.7 Product photo 
1.2	Registration name	DocuCentre-V C7785 (For Japan)	
1.3	Model name / number	DocuCentre-V C7785	
1.4	Main specifications of product	Print speed (Color/Mono): 70ppm/75ppm Paper size: SRA3(320x450mm) maximum Capable of duplex printing, facsimile and scanning Product Size: 700(W)x804(D)x1154(H) (mm) Product weight: 240kg	
1.5	CFP quantification unit	Per unit product	
1.6	CFP release date	2016/7/12	

2. Company Information		
2.1	Company name (in English)	Fuji Xerox Co., Ltd.
2.2	Phone number (incl. area code)	+81-3-6271-5111

3. CFP quantification results, and description of CFP declaration			
3.1	CFP quantification results	6,200	kg-CO ₂ e
3.2	Breakdown (by life cycle stage, by process, by flow, etc.)		
	Raw material acquisition stage	1,300	kg-CO ₂ e
	Production stage	100	kg-CO ₂ e
	Distribution stage	43	kg-CO ₂ e
	Use & maintenance stage	4,700	kg-CO ₂ e
	Disposal & recycling stage	63	kg-CO ₂ e
3.3	Value in CFP mark and description of additional info.		
	Value in CFP mark	<Numerical value> 6,200 kg	<Unit for the value> per unit product
	Description of additional info.	<p>*Calculated by the standard Scenario for MFP (EP type) *CO₂ emission in the distribution stage assumes Japan as the main sales area. *Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption-rate in Japan. *The CO₂ emission due to printing paper is excluded from the use and maintenance stage. *Print volume is assumed 2,940,000 sheets.</p> <div style="display: flex; align-items: center;">  <div style="margin-left: 20px;"> <p>21%</p> <p>76%</p> <ul style="list-style-type: none"> ■ Raw material acquisition stage ■ Production stage ■ Distribution stage ■ Use & maintenance stage ■ Disposal & recycling stage </div> </div>	
3.4	Remarks	<p>*Print volume: 2,940,000 sheets *In this scenario, the CO₂ emissions from copy papers are estimated 23,000 kg-CO₂e at 4.0 g per A4 paper.</p>	

4. Interpretation of CFP quantification results		
4.1	Interpretation of CFP quantification results	<p>CO2 emission in use and maintenance stage is the largest as 76%. It is important to save energy during product usage. The use condition in this scenario can be different from the use condition of the user.</p> <p>A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during product usage. For example, 1,170kg-CO2e of the CO2 emissions (approximately 19%) can be reduced if 2-in-1 print is applied to 1,470,000sheets (50% of print volume).</p> <p>Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as the rough estimate according to the reason mentioned above.</p>

5. Conditions of quantification					
5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-01
5.3	Assumptions of secondary data used	Basic secondary data v.1.01 is preferentially used. Available secondary data (country v.1.04, foreign country v.1.01) is used if the items don't correspond to basic data v.1.01.			

6. Verification information					
6.1	Verification method	Product-by-product	6.2	CFP system certification No.	—
6.3	Verification ID	CV-DG01-16047	6.4	Completion date of verification	2016/7/5

7. Program information					
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	http://www.cfp-japan.jp/
7.3	Program operator	Japan Environmental Management Association for Industry (JEMAI)	7.4	Address	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

8	Remarks	—
---	---------	---

For secondary data, please refer to the information on the following CFP website.
<http://www.cfp-japan.jp/calculate/verify/data.html>