



Registration Information Carbon Footprint of Products (CFP)



1. Product information			
1.1	Registration number	CR-DG01-15015	1.7 Product photo 
1.2	Product name	Dell Color Multifunction Printer C3765dnf	
1.3	Model name / number	Dell Color Multifunction Printer C3765dnf	
1.4	Main specifications of product	Print speed : 36ppm Paper size: A4 maximum Capable of duplex printing, facsimile and scanning Product Size: 439(W)x530(D)x558(H) (mm) Product weight: 32.6kg	
1.5	CFP quantification unit	Per unit product	
1.6	CFP release date	2015/3/31	

2. Company Information		
2.1	Company name (in English)	Fuji Xerox Co., Ltd.
2.2	Phone number (incl. area code)	+81-3-6271-5111

3. CFP quantification results, and description of CFP declaration			
3.1	CFP quantification results	2,300	kg-CO ₂ e
3.2	Breakdown (by life cycle stage, by process, by flow, etc.)		
	Raw material acquisition stage	230	kg-CO ₂ e
	Production stage	28	kg-CO ₂ e
	Distribution stage	21	kg-CO ₂ e
	Use & maintenance stage	2,000	kg-CO ₂ e
	Disposal & recycling stage	56	kg-CO ₂ e
3.3	Value and description of additional info.		
	Value to be stated on the mark	<Numerical value>	<Value on CFP mark>
		2,300kg	per unit product
Description of additional info.	<p>*Calculated by the standard Scenario for Printer (EP type) *CO₂ emission in the distribution stage assumes North America as the main sales area. *Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption-rate in North America. *The CO₂ emission due to printing paper is excluded from the use and maintenance stage. *Print volume is assumed 777,600 sheets.</p> <div style="display: flex; align-items: center;">  <div style="margin-left: 20px;"> <ul style="list-style-type: none"> ■ Raw material acquisition stage ■ Production stage ■ Distribution stage ■ Use & maintenance stage ■ Disposal & recycling stage </div> </div>		
3.4	Remarks	*Print volume: 777,600 sheets *In this scenario, the CO ₂ emissions from copy papers are estimated 6,000 kg-CO ₂ e at 4.0 g per A4 paper.	

4. Interpretation of CFP quantification results		
4.1	Interpretation of CFP quantification results	<p>CO₂ emission in use and maintenance stage is the largest as 86%. It is important to save energy during product usage. The use condition in this scenario can be different from the use condition of the user.</p> <p>A choice of the use condition (print mode, print conditions and so on) can reduce the CO₂ emission during product usage. For example, 385kg-CO₂e of the CO₂ emissions (approximately 16%) can be reduced if 2-in-1 print is applied to 388,800sheets (50% of print volume).</p> <p>Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as the rough estimate according to the reason mentioned above.</p>

5. Conditions of quantification					
5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-01
5.3	Assumptions of secondary data used	Basic secondary data v.1.01 is preferentially used. Available secondary data (country v.1.04, foreign country v.1.01) is used if the items don't correspond to basic data v.1.01.			

6. Verification information					
6.1	Verification method	Product-by-product	6.2	CFP system certification No.	—
6.3	Verification ID	CV-DG01-15015	6.4	Completion date of verification	2015/3/27

7. Program information					
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	http://www.cfp-japan.jp/
7.3	Program operator	Japan Environmental Management Association for Industry (JEMAI)	7.4	Address	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

8	Remarks	—
---	---------	---

For secondary data, please refer to the information on the following CFP website.
<http://www.cfp-japan.jp/calculate/verify/data.html>