## Registration Information Carbon Footprint of Products (CFP)



1. Pro	duct information		
1.1	Registration number	CR-DG01-15029	1.7 Product photo
1.2	Product name	Dell Color Cloud Multifunction Printer H625cdw	
1.3	Model name / number	Dell Color Cloud Multifunction Printer H625cdw	
1.4	Main specifications of product	Print speed (Letter): 25ppm color/black-and-white Paper size: A4 maximum Capable of duplex printing, facsimile, scanning, NFC and Wifi Product Size: 429(W)x503.5(D)x500(H) (mm) Product weight: 29.2kg	
1.5	CFP quantification unit	Per unit product	· · · · ·
1.6	CFP release date	2015/10/29	

2. Co	mpany Information	
2.1	Company name (in English)	Fuji Xerox Co., Ltd.
2.2	Phone number (incl. area code)	+81-3-6271-5111

3. CFF	P quantification results, ar	d description of CFP declration	
3.1	CFP quantification results	1,200	kg-CO <sub>2</sub> e
	Breakdown (by life cyc	le stage, by process, by flow, etc.)	
	Raw material acquisition stage	180	kg-CO <sub>2</sub> e
3.2	Production stage	25	kg-CO <sub>2</sub> e
3.2	Distribution stage	21	kg-CO <sub>2</sub> e
	Use & maintenance stage	910	kg-CO <sub>2</sub> e
	Disposal & recycling stage	47	kg-CO <sub>2</sub> e
	Value and description of	additional info.	
	Value to be stated	<numerial value=""></numerial>	<value cfp="" mark="" on=""></value>
	on the mark	1,200kg	per unit product
Description of additional info. Description of additional info. Description of additional info. Description of additional info. The public electric-power-consumption -rate in North America. *The CO <sub>2</sub> emission due to printing paper is excluded from the use and maintenance stage. *Print volume is assumed 375,000 sheets.		a main a with imption ting T <sup>7%</sup> T <sup>5%</sup> Braw material acquisition stage Production stage Distribution stage Use & maintenance stage Disposal & recycling stage	
3.4	Remarks	*Print volume: 375,000 sheets *In this scenario, the $CO_2$ emissio g per A4 paper.	ns from copy papers are estimated 2,900 kg-CO $_{2}$ e at 4.0

4. Inte	rpretation of CFP quantifi	cation results
4.1	Interpretation of CFP quantification results	CO <sub>2</sub> emission in use and maintenance stage is the largest as 77%. It is important to save energy during product usage. The use condition in this scenario can be different from the use condition of the user. A choice of the use condition (print mode, print conditions and so on) can reduce the CO <sub>2</sub> emission during product usage. For example, 227kg-CO <sub>2</sub> e of the CO <sub>2</sub> emissions (approximately 19%) can be reduced if 2-in-1 print is applied to 187,500sheets (50% of print volume). Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as the rough estimate according to the reason mentioned above.

ľ	5. Con	ditions of quantification				
	5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-01
	5.3	Assumptions of	Basic secondary data v.1 (country v.1.04, foreign co basic data v.1.01.			

6. Vei	6. Verification information				
6.1	Verification method	Product-by-product	6.2	CFP system certification No.	_
6.3	Verification ID	CV-DG01-15029	6.4	Valid period of verification	2015/10/13

7. Program information					
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	http://www.cfp-japan.jp/
7.3	Program operator	Japan Environmental Management Association for Industry (JEMAI)	7.4	Address	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

	8	Remarks	—
--	---	---------	---

For secondary data, please refer to the information on the following CFP website. http://www.cfp-japan.jp/calculate/verify/data.html