## Registration information of Carbon Footprint of Products

1. Product information			
1.1	Registration number	CR-DG01-14007	1.7 Product photo
1.2	Product name	Dell C2660dn Color Laser Printer	
1.3	Product model	Dell C2660dn Color Laser Printer	
1.4	Main specifications of product	Print speed (Letter/A4): 27ppm color/black-and-white Paper size: A4 maximum Capable of duplex printing Product Size: 439(W)x485(D)x379(H) (mm) Product weight: 25.6kg	
1.5	CFP quantification unit	Per unit product	
1.6	Date of release	2014/3/4	

2	2. Company Information		
	2.1	Company name	Fuji Xerox Co., Ltd.
	2.2	Phone number	+81-3-6271-5111

3. CFP quantification results, and contents of CFP decIration			
3.1	CFP quantification results	1,400	kg-CO <sub>2</sub> e (CFP quantification results can be slightly different from sum of thefollowing breakdown for rounding of fractions.)
	Breakdown (by life cyc	le stage, by process, by flow, etc.)	
	Raw material acquisition stage	160	kg-CO <sub>2</sub> e
3.2	Production stage	28	kg-CO <sub>2</sub> e
3.2	Distribution stage	19	kg-CO <sub>2</sub> e
	Use & maintenance stage	1,100	kg-CO <sub>2</sub> e
	Disposal & recycling stage	46	kg-CO₂e
	Value in a mark, and co	ntents of additional info.	
		<contents></contents>	<unit a="" for="" in="" mark="" the="" value=""></unit>
	Value in a mark	1,400 kg	per unit product
3.3	Contents of additional info.	electric-power-consumption-ra	Production stage Distribution stage Use & maintenance stage Disposal & recycling stage  maintenance stage is evaluated with the public
3.4	Remarks	*Print volume: 437,000 sheets *In this scenario, the $\rm CO_2$ emissions from copy papers are estimated 3,400 kg- $\rm CO_2$ e at 4.0 g per A4 paper.	

4. Inte	4. Interpretation of CFP quantification results		
4.1	Interpretation of CFP quantification results	CO <sub>2</sub> emission in use and maintenance stage is the largest as 81%. It is important to save energy during product usage.  The use condition in this scenario can be different from the use condition of the user. A choice of the use condition (print mode, print conditions and so on) can reduce the CO <sub>2</sub> emission during product usage.  For example, 185kg-CO <sub>2</sub> e of the CO <sub>2</sub> emissions (approximately 14%) can be reduced if 2-in-1 print is applied to 219,000sheets (50% of print volume).  CO <sub>2</sub> emission in raw material acquisition stage is the second largest as 12%. It is also important to reduce size and weight.  Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as the rough estimate according to the reason mentioned above.	

L	5. Conditions of quantification					
	5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-01
	5.3		Basic secondary data v.1.0 v.1.04, foreign country v.1.0			le secondary data (country rrespond to basic data v.1.01.

I	6. Verification information					
	6.1	Verification method	Product-by-product	6.2	CFP system certification No.	_
	6.3	Verification ID	CV-DG01-14007	6.4	Completion date of verification	2014/2/21

_	_		
	7	Remarks	_

<sup>(\*)</sup> For secondary data, refer to the following page on the CFP website. http://www.cfp-japan.jp/calculate/verify/data.html