



# Registration Information Carbon Footprint of Products (CFP)



1. Product information			
1.1	Registration number	CR-DG01-16066	1.7 Product photo  
1.2	Registration name	Dell Color Smart Printer   S3840cdn	
1.3	Model name / number	Dell Color Smart Printer   S3840cdn	
1.4	Main specifications of product	Print speed (Color/Mono): 35ppm/35ppm Paper size: A4 Capable of duplex printing Product Size: 454(W)x485(D)x439(H) (mm) Product weight: 26kg	
1.5	CFP quantification unit	Per unit product	
1.6	CFP release date	November 29th, 2016	

2. Company Information		
2.1	Company name (in English)	Fuji Xerox Co., Ltd.
2.2	Phone number (incl. area code)	+81-3-6271-5111

3. CFP quantification results, and description of CFP declaration												
3.1	CFP quantification results	2,300	kg-CO <sub>2</sub> e									
3.2	Breakdown (by life cycle stage, by process, by flow, etc.)											
	Raw material acquisition stage	190	kg-CO <sub>2</sub> e									
	Production stage	4.9	kg-CO <sub>2</sub> e									
	Distribution stage	40	kg-CO <sub>2</sub> e									
	Use & maintenance stage	2,000	kg-CO <sub>2</sub> e									
	Disposal & recycling stage	50	kg-CO <sub>2</sub> e									
3.3	Value in CFP mark and description of additional info.											
	Value in CFP mark	<Numerical value> <b>2,300 kg</b>	<Unit for the value> per unit product									
	Description of additional info.	<p>*Calculated by the standard Scenario for MFP (EP type)                      *CO<sub>2</sub> emission in the distribution stage assumes the United States as the main sales area.                      *Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption-rate in the United States.                      *Print volume is assumed 735,000 sheets.                      *In this scenario, the CO<sub>2</sub> emissions from copy papers are estimated 5,700 kg-CO<sub>2</sub>e at 4.0 g per A4 paper.                      *The CO<sub>2</sub> emission of printing paper is excluded from the use and maintenance stage.</p> <div style="text-align: center;">  <p>88%      8%</p> </div> <div style="margin-left: auto; margin-right: 0;"> <table border="1" style="font-size: small;"> <tr> <td><span style="color: blue;">■</span></td> <td>Raw material acquisition stage</td> </tr> <tr> <td><span style="color: red;">■</span></td> <td>Production stage</td> </tr> <tr> <td><span style="color: green;">■</span></td> <td>Distribution stage</td> </tr> <tr> <td><span style="color: purple;">■</span></td> <td>Use &amp; maintenance stage</td> </tr> <tr> <td><span style="color: yellow;">■</span></td> <td>Disposal &amp; recycling stage</td> </tr> </table> </div>		<span style="color: blue;">■</span>	Raw material acquisition stage	<span style="color: red;">■</span>	Production stage	<span style="color: green;">■</span>	Distribution stage	<span style="color: purple;">■</span>	Use & maintenance stage	<span style="color: yellow;">■</span>
<span style="color: blue;">■</span>	Raw material acquisition stage											
<span style="color: red;">■</span>	Production stage											
<span style="color: green;">■</span>	Distribution stage											
<span style="color: purple;">■</span>	Use & maintenance stage											
<span style="color: yellow;">■</span>	Disposal & recycling stage											
3.4	Remarks											

4. Interpretation of CFP quantification results	
4.1	<p>Interpretation of CFP quantification results</p> <p>CO2 emission in use and maintenance stage is the largest as 88%. It is important to save energy during product usage.</p> <p>The use condition in this scenario can be different from the use condition of the user.</p> <p>A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during product usage.</p> <p>For example, 505kg-CO2e of the CO2 emissions (approximately 22%) can be reduced if 2-in-1 print is applied to 367,500sheets (50% of print volume).</p> <p>Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as the rough estimate according to the reason mentioned above.</p>

5. Conditions of quantification					
5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-01
5.3	Assumptions of secondary data used	Basic secondary data v.1.01 is preferentially used. Available secondary data (country v.1.04, foreign country v.1.01) is used if the items don't correspond to basic data v.1.01.			

6. Verification information					
6.1	Verification method	Product-by-product	6.2	CFP system certification No.	—
6.3	Verification ID	CV-DG01-16066	6.4	Completion date of verification	November 16th, 2016

7. Program information					
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	<a href="http://www.cfp-japan.jp/">http://www.cfp-japan.jp/</a>
7.3	Program operator	Japan Environmental Management Association for Industry (JEMAI)	7.4	Address	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

8	Remarks	—
---	---------	---

For secondary data, please refer to the information on the following CFP website.  
<http://www.cfp-japan.jp/calculate/verify/data.html>