Registration Information Carbon Footprint of Products (CFP)



1. Product information				
1.1	Registration number	CR-DG02-17077	1.7 Product photo	
1.2	Registration name	Registration name Xerox VersaLink B605 Multifunction Printer (Tall type)		
1.3	Model name / number	Xerox VersaLink B605 Multifunction Printer (Tall type)		
1.4	Main specifications of product	Print speed (Mono): 58ppm (Letter) Maximum Paper size: Legal(215.9×355.6mm) Capable of print/copy/scan/FAX, duplex printing, NFC. %print/copy/scan model is available as well. %Finisher enclosed in a red frame in the product photo is provided as an optional item. Product Size: 470.0(W)x502.8(D)x843.7(H) (mm) Product weight: 32.5kg		
1.5	CFP quantification unit	Per unit product	_	
1.6	CFP release date	July 27th, 2017		

2. Cor	2. Company Information			
2.1	Company name (in English)	Fuji Xerox Co., Ltd.		
2.2	Phone number (incl. area code)	+81-3-6271-5111		

3.1 CFP quantification results Breakdown (by life cycle stage, by process, by flow, etc.) Raw material acquisition stage 220 kg-CO₂e Production stage 230 kg-CO₂e Use & maintenance stage Distribution stage 247 kg-CO₂e Use & maintenance stage Distribution stage 257 kg-CO₂e Use & maintenance stage Disposal & recycling stage Value in CFP mark and description of additional info. *Numerial value> *Value in CFP mark 2,300kg Per unit product *Calculated by the standard Scenario for MFP (EP type). *Calculated on the model with print/copy/scan/FAX functions. *The difference in weight with the print/copy/scan model is 150g, which accounts for 0.5% of the product weight. *Calculated on the basic configuration, which is not equipped with the optional finisher enclosed in a red frame in the product photo. *CO₂ emission in the distribution stage assumes the United States as the main sales area. *Flectric power in the use and maintenance stage is evaluated with the public electric-power-consumption-rate in the United States. *Print volume is assumed 2,018,000 sheets. *In this scenario, the CO₂ emissions from copy papers are estimated 16,000 kg-CO₂e at 4.0g per A4 paper. *The CO₂ emission of printing paper is excluded from the use and maintenance stage. Disposal & recycling stage Distribution stage 1% Production stage 0.1% Distribution stage 1%	3. CFF	. CFP quantification results, and description of CFP declration				
Raw material acquisition stage Production stage 3.3 kg-CO2e Use & maintenance stage 2,000 kg-CO2e Disposal & recycling stage 13 kg-CO2e Disposal & recycling stage Value in CFP mark and description of additional info. *Numerial value> *Calculated by the standard Scenario for MFP (EP type). *Calculated on the model with print/copy/scan/FAX functions. *The difference in weight with the print/copy/scan/FAX functions. *Calculated on the basic configuration, which is not equipped with the optional finisher enclosed in a red frame in the product photo. *CO2 emission in the distribution stage assumes the United States as the main sales area. *Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption-rate in the United States. *Print volume is assumed 2,018,000 sheets. *In this scenario, the CO2 emissions from copy papers are estimated 16,000 kg-CO2e at 4.0g per A4 paper. *The CO2 emission of printing paper is excluded from the use and maintenance stage. Disposal & recycling stage Disposal & recycling stage Disposal & recycling stage Disposal & recycling stage Distribution stage 0.1% Distribution stage 0.1% Distribution stage 0.1%		CFP quantification		kg-CO2e		
Stage Production stage 3.3 kg-CO ₂ e			e stage, by process, by flow, etc.)			
Distribution stage Use & maintenance stage Disposal & recycling stage Value in CFP mark and description of additional info. **Calculated by the standard Scenario for MFP (EP type). **Calculated on the model with print/copy/scan/FAX functions. *The difference in weight with the print/copy/scan/FAX functions. *Calculated on the basic configuration, which is not equipped with the optional finisher enclosed in a red frame in the product photo. *CO2_ emission in the distribution stage assumes the United States as the main sales area. *Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption-rate in the United States. *Print volume is assumed 2,018,000 sheets. *In this scenario, the CO2_ emissions from copy papers are estimated 16,000 kg-CO2_e at 4.0g per A4 paper. *The CO2_ emission of printing paper is excluded from the use and maintenance stage. *Raw material acquisition stage 10% Distribution stage 0.11% Distribution stage 1% Distribution stage 1%		·	220	kg-CO₂e		
Distribution stage Use & maintenance stage Disposal & recycling stage Value in CFP mark and description of additional info. **Numerial value** **Calculated by the standard Scenario for MFP (EP type). **Calculated on the model with print/copy/scan/FAX functions. *The difference in weight with the print/copy/scan model is 150g, which accounts for 0.5% of the product weight. **Calculated on the basic configuration, which is not equipped with the optional finisher enclosed in a red frame in the product photo. **CO2** emission in the distribution stage assumes the United States as the main sales area. **Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption-rate in the United States. **Print volume is assumed 2,018,000 sheets. **In this scenario, the CO2** emissions from copy papers are estimated 16,000 kg-CO2** at 4.0g per A4 paper. **The CO2** emission of printing paper is excluded from the use and maintenance stage. Disposal & recycling stage Disposal & recycling stage **The CO2** emission of printing paper is excluded from the use and maintenance stage. Raw material acquisition stage 1%* Distribution stage 1%* Distribution stage 1%*	2 2	Production stage	3.3	kg-CO ₂ e		
Disposal & recycling stage Value in CFP mark and description of additional info. Value in CFP mark 2,300kg Per unit product *Calculated by the standard Scenario for MFP (EP type). *Calculated on the model with print/copy/scan/FAX functions. *The difference in weight with the print/copy/scan model is 150g, which accounts for 0.5% of the product weight. *Calculated on the basic configuration, which is not equipped with the optional finisher enclosed in a red frame in the product photo. *CO ₂ emission in the distribution stage assumes the United States as the main sales area. *Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption-rate in the United States. *Print volume is assumed 2,018,000 sheets. *In this scenario, the CO ₂ emissions from copy papers are estimated 16,000 kg-CO ₂ e at 4.0g per A4 paper. *The CO ₂ emission of printing paper is excluded from the use and maintenance stage. Disposal & recycling stage Disposal & recycling stage 1% Production stage 0.1% Distribution stage 1%	3.2	Distribution stage	27	kg-CO ₂ e		
Value in CFP mark and description of additional info. Value in CFP mark Square Square		Use & maintenance stage	2,000	kg-CO₂e		
Value in CFP mark 2,300kg per unit product *Calculated by the standard Scenario for MFP (EP type). *Calculated on the model with print/copy/scan/FAX functions. *The difference in weight with the print/copy/scan model is 150g, which accounts for 0.5% of the product weight. *Calculated on the basic configuration, which is not equipped with the optional finisher enclosed in a red frame in the product photo. *CO2 emission in the distribution stage assumes the United States as the main sales area. *Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption-rate in the United States. *Print volume is assumed 2,018,000 sheets. *In this scenario, the CO2 emissions from copy papers are estimated 16,000 kg-CO2 at 4.0g per A4 paper. *The CO2 emission of printing paper is excluded from the use and maintenance stage. Disposal & recycling stage Disposal & recycling stage 1% Production stage 0.1% Distribution stage 1%		, , , ,		kg-CO ₂ e		
*Calculated by the standard Scenario for MFP (EP type). *Calculated on the model with print/copy/scan/FAX functions. *The difference in weight with the print/copy/scan model is 150g, which accounts for 0.5% of the product weight. *Calculated on the basic configuration, which is not equipped with the optional finisher enclosed in a red frame in the product photo. *CO ₂ emission in the distribution stage assumes the United States as the main sales area. *Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption-rate in the United States. *Print volume is assumed 2,018,000 sheets. *In this scenario, the CO ₂ emissions from copy papers are estimated 16,000 kg-CO ₂ e at 4.0g per A4 paper. *The CO ₂ emission of printing paper is excluded from the use and maintenance stage. Disposal & recycling stage Disposal & recycling stage 1% Production stage 0.1% Distribution stage 1%		Value in CFP mark and d				
*Calculated by the standard Scenario for MFP (EP type). *Calculated on the model with print/copy/scan/FAX functions. *The difference in weight with the print/copy/scan model is 150g, which accounts for 0.5% of the product weight. *Calculated on the basic configuration, which is not equipped with the optional finisher enclosed in a red frame in the product photo. *CO ₂ emission in the distribution stage assumes the United States as the main sales area. *Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption-rate in the United States. *Print volume is assumed 2,018,000 sheets. *In this scenario, the CO ₂ emissions from copy papers are estimated 16,000 kg-CO ₂ e at 4.0g per A4 paper. *The CO ₂ emission of printing paper is excluded from the use and maintenance stage. Disposal & recycling stage Disposal & recycling stage 1% Production stage 0.1% Distribution stage 10% Distribution stage 10%			<numerial value=""></numerial>	<unit for="" the="" value=""></unit>		
*Calculated on the model with print/copy/scan/FAX functions. *The difference in weight with the print/copy/scan model is 150g, which accounts for 0.5% of the product weight. *Calculated on the basic configuration, which is not equipped with the optional finisher enclosed in a red frame in the product photo. *CO ₂ emission in the distribution stage assumes the United States as the main sales area. *Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption-rate in the United States. *Print volume is assumed 2,018,000 sheets. *In this scenario, the CO ₂ emissions from copy papers are estimated 16,000 kg-CO ₂ e at 4.0g per A4 paper. *The CO ₂ emission of printing paper is excluded from the use and maintenance stage. Disposal & recycling stage Disposal & recycling stage 1% Production stage 0.1% Distribution stage 1%		Value in CFP mark	2,300kg	per unit product		
3.4 Remarks	3.3	•	*Calculated on the model with print/copy/scan/FAX functions. *The difference in weight with the print/copy/scan model is 150g, which accounts for 0.5% of the product weight. *Calculated on the basic configuration, which is not equipped with the optional finisher enclosed in a red frame in the product photo. *CCO2 emission in the distribution stage assumes the United States as the main sales area *Electric power in the use and maintenance stage is evaluated with the public electric- power-consumption-rate in the United States. *Print volume is assumed 2,018,000 sheets. *In this scenario, the CO2 emissions from copy papers are estimated 16,000 kg-CO2 at 4.0g per A4 paper. *The CO2 emission of printing paper is excluded from the use and maintenance stage. Disposal & recycling stage Disposal & recycling stage **Print volume is assumed 2,018,000 sheets.** *The CO2 emission of printing paper is excluded from the use and maintenance stage. Disposal & recycling stage **Distribution stage 10% Distribution stage 10%			
	3.4	Remarks				

4. Inte	4. Interpretation of CFP quantification results				
4. Inte	Interpretation of CFP	CO2 emission in use and maintenance stage is the largest as 88%. It is important to save energy during product usage. The use condition in this scenario can be different from the use condition of the user. A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during product usage. For example, 500kg-CO2e of the CO2 emissions (approximately 22%) can be reduced if 2-in-1 print is applied to 1,009,000 sheets (50% of the estimated total print volume). Primary data is used in the raw material consumption. Secondary data is used in			
		the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as the rough estimate according to the reason mentioned above.			

5. Cor	5. Conditions of quantification				
5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-02
5.3	Assumptions of		Basic secondary data v.1.01 is preferertially used. Available secondary data country v.1.04, foreign country v.1.01) is used if the items don't correspond to pasic data v.1.01.		

6. Verification information					
6.1	Verification method	Product-by-product	6.2	CFP system certification No.	_
6.3	Verification ID	CV-DG02-17077	6.4	Completion date of verification	July 21st, 2017

7. Pro	7. Program information				
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	http://www.cfp-japan.jp/
7.3	Program operator	Japan Environmental Management Association for Industry (JEMAI)	7.4	Address	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

I	8	Remarks	_

For secondary data, please refer to the information on the following CFP website. http://www.cfp-japan.jp/calculate/verify/data.html