Registration Information Carbon Footprint of Products (CFP)



1. Pro	1. Product information						
1.1	Registration number	CR-DG02-17075	1.7 Product photo				
1.2	Registration name	Xerox VersaLink B605 Multifunction Printer					
1.3	Model name / number						
Main specifications of product Main specifications of product Maximum Paper size: Legal(215 Capable of print/copy/scan/FAX printing, NFC. **print/copy/scan model is availaded Product Size: 470.0(W)x502.8(D)		Print speed (Mono): 58ppm (Letter) Maximum Paper size: Legal(215.9×355.6mm) Capable of print/copy/scan/FAX(%), duplex printing, NFC. %print/copy/scan model is available as well. Product Size: 470.0(W)x502.8(D)x643.7(H) (mm) Product weight: 30.5kg					
1.5	CFP quantification unit	Per unit product	_				
1.6	CFP release date	July 27th, 2017					

2. Cor	2. Company Information					
2.1	Company name (in English)	Fuji Xerox Co., Ltd.				
2.2	Phone number (incl. area code)	+81-3-6271-5111				

3. CFF	. CFP quantification results, and description of CFP declration				
3.1	CFP quantification results	2,300	kg-CO2e		
	Breakdown (by life cyc	le stage, by process, by flow, etc.)			
	Raw material acquisition stage	220	kg-CO₂e		
3.2	Production stage	3.3	kg-CO ₂ e		
3.2	Distribution stage	26	kg-CO ₂ e		
	Use & maintenance stage	2,000	kg-CO₂e		
	Disposal & recycling stage	13	kg-CO₂e		
	Value in CFP mark and d	escription of additional info.			
		<numerial value=""></numerial>	<unit for="" the="" value=""></unit>		
	Value in CFP mark	2,300kg	per unit product		
3.3	Description of additional info.	*The difference in weight with for 0.5% of the product weight *CO ₂ emission in the distribution sales area. *Electric power in the use and electric-power-consumption-rate *Print volume is assumed 2,01 *In this scenario, the CO ₂ emis CO ₂ e at 4.0g per A4 paper.	on stage assumes the United States as the main maintenance stage is evaluated with the public te in the United States.		
3.4	Remarks				
J. T	Remains				

4. Inte	4. Interpretation of CFP quantification results					
		CO2 emission in use and maintenance stage is the largest as 88%. It is important to save energy during product usage.				
4.1		The use condition in this scenario can be different from the use condition of the user. A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during product usage. For example, 500kg-CO2e of the CO2 emissions (approximately 22%) can be reduced if 2-in-1 print is applied to 1,009,000 sheets (50% of the estimated total print volume).				
		Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as the rough estimate according to the reason mentioned above.				

5.	5. Conditions of quantification					
	5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-02
	5.3	Assumptions of	Basic secondary data v.1.01 is preferentially used. Available secondary data country v.1.04, foreign country v.1.01) is used if the items don't correspond to pasic data v.1.01.			

6. Veri	6. Verification information				
6.1	Verification method	Product-by-product	6.2	CFP system certification No.	-
6.3	Verification ID	CV-DG02-17075	6.4	Completion date of verification	July 21st, 2017

7. Program information					
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	http://www.cfp-japan.jp/
7.3	Program operator	Japan Environmental Management Association for Industry (JEMAI)	7.4	Δηητές	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

Γ	8	Remarks	_
_			

For secondary data, please refer to the information on the following CFP website. http://www.cfp-japan.jp/calculate/verify/data.html