Registration Information Carbon Footprint of Products (CFP)



1. Pro	duct information			
1.1	Registration number	CR-DG02-17051	1.7 Product photo	
1.2	Registration name	Xerox VersaLink B7030 Multifunction Printer (Desktop) Xerox VersaLink B7030 Multifunction Printer		
1.3	Model name / number			
1.4	Main specifications of product	Print speed (Mono): 30ppm (A4) Maximum Paper size: A3(297×420mm) Capable of print/copy/scan/fax, duplex printing, WiFi, NFC. Product Size: 590(W)x670.8(D)x767.9(H) (mm) Product weight: 53.1kg		
1.5	CFP quantification unit	Per unit product		
1.6	CFP release date	May 19th, 2017		

2. Cor	2. Company Information			
2.1	Company name (in English)	Fuji Xerox Co., Ltd.		
2.2	Phone number (incl. area code)	+81-3-6271-5111		

3. CFF	guantification results, an	d description of CFP declration	
3.1	CFP quantification results	1,300	kg-CO2e
		e stage, by process, by flow, etc.)	
	Raw material acquisition stage	250	kg-CO₂e
3.2	Production stage	10	kg-CO ₂ e
3.∠	Distribution stage	68	kg-CO ₂ e
	Use & maintenance stage	920	kg-CO ₂ e
	Disposal & recycling stage	25	kg-CO ₂ e
	Value in CFP mark and d	escription of additional info.	
		<numerial value=""></numerial>	<unit for="" the="" value=""></unit>
	Value in CFP mark	1,300kg	per unit product
3.3	Description of additional info.	sales area. *Electric power in the use and electric-power-consumption-ra *Print volume is assumed 540, *In this scenario, the CO ₂ emis CO ₂ e at 4.0g per A4 paper.	
3.4	Remarks		

4. Inte	4. Interpretation of CFP quantification results					
4. Inte	Interpretation of CED	CO2 emission in use and maintenance stage is the largest as 72%. It is important to save energy during product usage. The use condition in this scenario can be different from the use condition of the user. A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during product usage. For example, 228.75kg-CO2e of the CO2 emissions (approximately 18%) can be reduced if 2-in-1 print is applied to 50% of the estimated total print volume. Primary data is used in the raw material consumption. Secondary data is used in				
		the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as the rough estimate according to the reason mentioned above.				

5. C	5. Conditions of quantification					
5.	1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-02
5.3	3	Assumptions of secondary data used	Basic secondary data v.1.01 is preferertially used. Available secondary data (country v.1.04, foreign country v.1.01) is used if the items don't correspond to basic data v.1.01.			

6. Veri	6. Verification information				
6.1	Verification method	Product-by-product	6.2	CFP system certification No.	-
6.3	Verification ID	CV-DG02-17051	6.4	Completion date of verification	May 12th, 2017

7. Program information					
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	http://www.cfp-japan.jp/
7.3	Program operator	Japan Environmental Management Association for Industry (JEMAI)	7.4	Address	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

8	Remarks	_

For secondary data, please refer to the information on the following CFP website. http://www.cfp-japan.jp/calculate/verify/data.html