Registration Information Carbon Footprint of Products (CFP)



1. Product information						
1.1	Registration number	CR-DG02-17069	1.7 Product photo			
1.2	Registration name	Xerox VersaLink C600 Color Printer				
1.3	Model name / number	Xerox VersaLink C600 Color Printer	in a			
1.4	Main specifications of product	Print speed (Color/Mono): 55ppm/55ppm (Letter) Maximum Paper size: Legal(215.9×355.6mm) Capable of print, duplex printing, NFC. Product Size: 427.4(W)x465.5(D)x443.4(H) (mm) Product weight: 29.4kg				
1.5	CFP quantification unit	Per unit product				
1.6	CFP release date	July 14th, 2017				

2. Cor	2. Company Information					
2.1	Company name (in English)	Fuji Xerox Co., Ltd.				
2.2	Phone number (incl. area code)	+81-3-6271-5111				

3. CFF	o quantification results, an	d description of CFP declration		
3.1	CFP quantification results	3,300	kg-CO2e	
	Breakdown (by life cyc	le stage, by process, by flow, etc.)	
	Raw material acquisition stage	240	kg-CO₂e	
3.2	Production stage	5.1	kg-CO ₂ e	
3.2	Distribution stage	25	kg-CO ₂ e	
	Use & maintenance stage	3,000	kg-CO₂e	
	Disposal & recycling stage	16	kg-CO ₂ e	
	Value in CFP mark and d	lescription of additional info.		
		<numerial value=""></numerial>	<unit for="" the="" value=""></unit>	
	Value in CFP mark	3,300kg	per unit product	
3.3	Description of additional info.	*Calculated by the standard Scenario for Printer (EP type). *CO ₂ emission in the distribution stage assumes the United States as the sales area. *Electric power in the use and maintenance stage is evaluated with the pelectric-power-consumption-rate in the United States. *Print volume is assumed 1,815,000 sheets. *In this scenario, the CO ₂ emissions from copy papers are estimated 14, CO ₂ e at 4.0g per A4 paper. *The CO ₂ emission of printing paper is excluded from the use and mainten stage. Disposal & recycling stage 1% Production stage 0.2% Distribution stage 1%		
3.4	Remarks			

4. Interpretation of CFP quantification results					
4.11	Interpretation of CFP	CO2 emission in use and maintenance stage is the largest as 91%. It is important to save energy during product usage. The use condition in this scenario can be different from the use condition of the user. A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during product usage. For example, 750kg-CO2e of the CO2 emissions (approximately 23%) can be reduced if 2-in-1 print is applied to 907,500 sheets (50% of the estimated total print volume). Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as the rough estimate according to the reason mentioned above.			

5. C	5. Conditions of quantification					
5.	1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-02
5.3	3	Assumptions of secondary data used	Basic secondary data v.1.01 is preferertially used. Available secondary data (country v.1.04, foreign country v.1.01) is used if the items don't correspond to basic data v.1.01.			

6. Veri	6. Verification information					
6.1	Verification method	Product-by-product	6.2	CFP system certification No.	-	
6.3	Verification ID	CV-DG02-17069	6.4	Completion date of verification	July 10th, 2017	

7. Program information					
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	http://www.cfp-japan.jp/
7.3	Program operator	Japan Environmental Management Association for Industry (JEMAI)	7.4	Δηητές	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

Γ	8	Remarks	_
_			

For secondary data, please refer to the information on the following CFP website. http://www.cfp-japan.jp/calculate/verify/data.html