## Registration Information Carbon Footprint of Products (CFP)



1. Product information						
1.1	Registration number	CR-DG02-17065	1.7 Product photo			
1.2	Registration name	Xerox VersaLink C7000 Color Printer				
1.3	Model name / number	Xerox VersaLink C7000 Color Printer	E3 : 60			
1.4	Main specifications of product	Print speed (Color/Mono): 35ppm/35ppm (A4) Maximum Paper size: A3(297×420mm) Capable of print/copy/scan/fax, duplex printing, WiFi, NFC. Product Size: 590(W)x670.8(D)x637(H) (mm) Product weight: 51kg				
1.5	CFP quantification unit	Per unit product				
1.6	CFP release date	June 9th, 2017				

2. Co	2. Company Information				
2.1	Company name (in English)	Fuji Xerox Co., Ltd.			
2.2	Phone number (incl. area code)	+81-3-6271-5111			

3. CFF	. CFP quantification results, and description of CFP declration					
3.1	CFP quantification results	2,100	kg-CO2e			
		e stage, by process, by flow, etc.)				
	Raw material acquisition stage	340	kg-CO₂e			
3.2	Production stage	5.3	kg-CO <sub>2</sub> e			
3.2	Distribution stage	68	kg-CO <sub>2</sub> e			
	Use & maintenance stage	1,700	kg-CO₂e			
	Disposal & recycling stage	34	kg-CO₂e			
	Value in CFP mark and d	escription of additional info.				
		<numerial value=""></numerial>	<unit for="" the="" value=""></unit>			
	Value in CFP mark	2,100kg	per unit product			
3.3	Description of additional info.	*Calculated by the standard Scenario for Printer (EP type).  *CO <sub>2</sub> emission in the distribution stage assumes the United States as the main sales area.  *Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption-rate in the United States.  *Print volume is assumed 735,000 sheets.  *In this scenario, the CO <sub>2</sub> emissions from copy papers are estimated 5,700 kg-CO <sub>2</sub> e at 4.0g per A4 paper.  *The CO <sub>2</sub> emission of printing paper is excluded from the use and maintenance stage.  Disposal & recycling stage  Disposal & recycling stage  Raw material acquisition stage 16%  Production stage 0.2%  Distribution stage 3%				
3.4	Remarks					
<u> </u>	Romano					

4.	4. Interpretation of CFP quantification results					
	Inte	Interpretation of CED	CO2 emission in use and maintenance stage is the largest as 79%. It is important to save energy during product usage.  The use condition in this scenario can be different from the use condition of the user.  A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during product usage.  For example, 420kg-CO2e of the CO2 emissions (approximately 20%) can be reduced if 2-in-1 print is applied to 367,500sheets (50% of print volume).  Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own			
		quantification results	Primary data is used in the raw material consumption. Secondary data is used in			

5. Co	5. Conditions of quantification				
5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-02
5.3	Assumptions of secondary data used	Basic secondary data v.1.01 is preferentially used. Available secondary data country v.1.04, foreign country v.1.01) is used if the items don't correspond to easic data v.1.01.			

6. Veri	6. Verification information					
6.1	Verification method	Product-by-product	6.2	CFP system certification No.	-	
6.3	Verification ID	CV-DG02-17065	6.4	Completion date of verification	June 2nd, 2017	

7. Pro	7. Program information				
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	http://www.cfp-japan.jp/
7.3	Program operator	Japan Environmental Management Association for Industry (JEMAI)	7.4	Address	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

Γ	8	Remarks	_
_			

For secondary data, please refer to the information on the following CFP website. http://www.cfp-japan.jp/calculate/verify/data.html