Registration Information Carbon Footprint of Products (CFP)



1. Product information					
1.1	Registration number	CR-DG02-17063	1.7 Product photo		
1.2	Registration name	Xerox VersaLink C7030 Color Multifunction Printer (3TM)			
1.3	Model name / number	Xerox VersaLink C7030 Color Multifunction Printer (3TM)			
1.4	Main specifications of product	Print speed (Color/Mono): 30ppm/30ppm (A4) Maximum Paper size: A3(297×420mm) Capable of print/copy/scan/fax, duplex printing, WiFi, NFC. Product Size: 615.7(W)x670.8(D)x1118.6(H) (mm) Product weight: 93kg			
1.5	CFP quantification unit	Per unit product			
1.6	CFP release date	June 9th, 2017			

2. Co	2. Company Information			
2.1	Company name (in English)	Fuji Xerox Co., Ltd.		
2.2	Phone number (incl. area code)	+81-3-6271-5111		

3. CFF	CFP quantification results, and description of CFP declration					
3.1	CFP quantification results	1,700	kg-CO2e			
	Breakdown (by life cycl	e stage, by process, by flow, etc.)				
	Raw material acquisition stage	490	kg-CO ₂ e			
3.2	Production stage	12	kg-CO ₂ e			
3.2	Distribution stage	110	kg-CO ₂ e			
	Use & maintenance stage	1,000	kg-CO ₂ e			
	Disposal & recycling stage	64	kg-CO ₂ e			
	Value in CFP mark and d	escription of additional info.				
		<numerial value=""></numerial>	<unit for="" the="" value=""></unit>			
	Value in CFP mark	1,700kg	per unit product			
3.3	Description of additional info.	1,700kg per unit product *Calculated by the standard Scenario for MFP (EP type). *CO ₂ emission in the distribution stage assumes the United States as the main sales area. *Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption-rate in the United States. *Print volume is assumed 540,000 sheets. *In this scenario, the CO ₂ emissions from copy papers are estimated 4,200 kg-CO ₂ e at 4.0g per A4 paper. *The CO ₂ emission of printing paper is excluded from the use and maintenance stage. Disposal & recycling stage 4% Use & maintenance stage 60%				
24	Domorko					
3.4	Remarks					

4. Inte	4. Interpretation of CFP quantification results					
4. Inte	Interpretation of CFP quantification results	CO2 emission in use and maintenance stage is the largest as 60%. It is important to save energy during product usage. The use condition in this scenario can be different from the use condition of the user. A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during product usage				
4.1	Interpretation of CFP quantification results	For example, 260kg-CO2e of the CO2 emissions (approximately 15%) can be reduced if 2-in-1 print is applied to 270,000sheets (50% of print volume). Primary data is used in the raw material consumption. Secondary data is used				

5. Cor	5. Conditions of quantification				
5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-02
5.3	Assumptions of	Basic secondary data v.1.01 is preferentially used. Available secondary data (country v.1.04, foreign country v.1.01) is used if the items don't correspond to basic data v.1.01.			

6. Veri	6. Verification information				
6.1	Verification method	Product-by-product	6.2	CFP system certification No.	-
6.3	Verification ID	CV-DG02-17063	6.4	Completion date of verification	June 2nd, 2017

7. Program information					
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	http://www.cfp-japan.jp/
7.3	Program operator	Japan Environmental Management Association for Industry (JEMAI)	7.4	Address	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

8	Remarks	_		
For oor	For according data, places refer to the information on the following CED website			

For secondary data, please refer to the information on the following CFP website. http://www.cfp-japan.jp/calculate/verify/data.html