Registration Information Carbon Footprint of Products (CFP)



1. Pro	duct information		
1.1	Registration number	CR-DG01-16041	1.7 Product photo
1.2	Registration name	Canon imageRUNNER ADVANCE C5550i	
1.3	Model name / number	Canon imageRUNNER ADVANCE C5550i	1111
1.4	Multifunction Copiers Main specifications of product Print speed (CL&BW): 50 ppm (LTR) 620mm(W)×741mm(D)×945mm(H) Product weight: Approximately 139kg		Comp.
1.5	CFP quantification unit	Per unit product	
1.6	CFP release date	8/16/2016	Cassette Feeding Unit is

2. Co	mpany Information	
2.1	Company name (in English)	Canon Inc.
2.2	Phone number (incl.	+81-3-3758-2111

0.055	D	d a set of OFD de election	
3. CFF	quantification results, ar	d contents of CFP decIration	l. 00
3.1	CFP quantification results	2,000	$kg\text{-}CO_2e$ (CFP quantification results can be slightly different from sum of the following breakdown for rounding of fractions.)
	Breakdown (by life cyc	le stage, by process, by flow, etc.)	
	Raw material acquisition stage	930	kg-CO ₂ e
3.2	Production stage	130	kg-CO₂e
0.2	Distribution stage	39	kg-CO₂e
	Use & maintenance stage	790	kg-CO ₂ e
	Disposal & recycling stage	110	kg-CO₂e
	Value and description of		
	Value to be stated	<numerial value=""></numerial>	<value cfp="" mark="" on=""></value>
	on the mark	2,000 kg	Per unit product
3.3	Contents of additional info.	Calculated in the following cor - the standard scenario for Mi Device (EP type), - Print volume: 1.5 million she - US market, - Printing paper is not conside	wultifunction recycling stage 5% Raw material
3.4	Remarks		_

4. Inte	rpretation of CFP quantifi	cation results
		·CO2 emission in Raw material acquisition stage is the largest as 47%. It is important to to reduce the size and weight, and to use low environmental impact materials.
4.1	•	·CO2 emission in Use & maintenance stage is the second largest as 40%. It is also important to save energy during product usage and to make the life time of consumables longer. The condition in this CFP evaluation can be different from the one which the user operates under. A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during Use & maintenance stage.
		·We evaluated the CFP with Canon's own data of raw materials weight and the general basic unit for the parts because it is difficult to collect the data for a couple of thousands of parts. Accordingly, the results may be different from the specific product specification. As such, please be advised that this result would be a rough estimate.
		As such, please be advised that this result would be a rough estimate.

ı	5. Con	ditions of quantification				
	5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-01
	5.3		Basic secondary data v.1 is used if the items don't o			ailable secondary data v.1.01 .01.

ı	6. Veri	ification information				
	6.1	Verification method	CFP System certification	6.2	CFP system certification No.	SCN14002
	6.3	Verification ID	CV-DG01-16039	6.4	Completion date of verification	6/22/2016

	7. Pro	gram information				
	7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	http://www.cfp-japan.jp/
ĺ	7.3	Program operator	Japan Environmental Management Association for	7.4	Address	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

8	Remarks
---	---------

^(*) For secondary data, refer to the following page on the CFP website. http://www.cfp-japan.jp/calculate/verify/data.html