Registration information of Carbon Footprint of Products

1. Product information							
1.1	Registration number	CR-DG01-15048	1.7 Product photo				
1.2	Product name	Canon imageRUNNER ADVANCE 6565i					
1.3	Product model	Canon imageRUNNER ADVANCE 6565i					
1.4	Main specifications of product	Multifunction Copiers Print speed (BW): 65 ppm (LTR) 670mm(W)×779mm(D)×1,220mm(H) Product weight: Approximately 234kg					
1.5	CFP quantification unit	Per unit product	a de la de l				
1.6	Date of release	2/24/2016	Finisher unit is excluded.				

2. Con	2. Company Information				
2.1	Company name	Canon Inc.			
2.2	Phone number	+81-3-3758-2111			

3. CFF	3. CFP quantification results, and contents of CFP declration					
3.1	CFP quantification results	2,900	kg-CO ₂ e (CFP quantification results can be slightly different from sum of the following breakdown for rounding of fractions.)			
	Breakdown (by life cycle	e stage, by process, by flow, etc.)				
	Raw material acquisition stage	1,300	kg-CO ₂ e			
	Production stage	65	kg-CO ₂ e			
3.2	Distribution stage	60	kg-CO ₂ e			
	Use & maintenance stage	1,400	kg-CO ₂ e			
	Disposal & recycling stage	120	kg-CO ₂ e			
	Value in a mark, and cor	ntents of additional info.				
		<contents></contents>	<unit a="" for="" in="" mark="" the="" value=""></unit>			
	Value in a mark	2,900kg	Per unit product			
3.3	Contents of additional info.	Calculated in the following cor - the standard scenario for Mu Device (EP type), - Print volume: 2.5 million she - US market, - Printing paper is not conside	nditions; Disposal & recycling stage 4% material acquisitio n stage 44% stage 44% use & maintena nce stage 48% Distributio n stage 2%			
3.4	Remarks		_			

. Interpretation of CFP quantification results						
Interpretation of CFP quantification results	 CO2 emission in Use & maintenance stage is the largest as 48%. It is important to save energy during product usage and to make the life time of consumables longer. The condition in this CFP evaluation can be different from the one which the user operates under. A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during Use & maintenance stage. CO2 emission in Raw material acquisition stage is the second largest as 44%. It is also important to reduce the size and weight, and to use low environmental impact materials. We evaluated the CFP with Canon's own data of raw materials weight and the general basic unit for the parts because it is difficult to collect the data for a couple of thousands of parts. Accordingly, the results may be different from the specific product specification. 					
	Interpretation of CFP quantification results					

5. Conditions of quantification					
5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-01
5.3	Assumptions of secondary data used	Basic secondary data v.1 is used if the items don't c	.01 is corres	preferentially used. Av pond to basic data v.1.	ailable secondary data v.1.01 .01.

6. Verification information						
6.1	Verification method	CFP System certification	6.2	CFP system certification No.	SCN14002	
6.3	Verification ID	CV-DG01-15028	6.4	Valid period of verification	12/25/2015	

7. Program information						
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	http://www.cfp-japan.jp/	
7.3	Program operator	Japan Environmental Management Association for Industry (JEMAI)	7.4	Address	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044	

Remarks 8 _

(*) For secondary data, refer to the following page on the CFP website. http://www.cfp-japan.jp/calculate/verify/data.html