Registration Information Carbon Footprint of Products (CFP)



1. Pro	duct information		
1.1	Registration number	CR-DG02-18053	1.7 Product photo
1.2	Registration name	Canon imageRUNNER ADVANCE C3525i III (For USA)	
1.3	Model name / number	Canon imageRUNNER ADVANCE C3525i III(For USA)	
1.4	Main specifications of product	Multifunction Copiers Print speed BW: 25 ppm / CL: 25 ppm (LTR) 565mm(W) × 742mm(D) × 1148mm(H) Product weight: Approximately 81kg	
1.5	CFP quantification unit	Per unit product	8 80
1.6	CFP release date	4/4/2019	Cassette Feeding Unit is excluded.

2. Cor	mpany Information	
2.1	Company name (in English)	Canon Inc.
2.2	Phone number (incl. area code)	+81-3-3758-2111

3.1 CFP quantification results 1,200 kg-CO2e (CFP quantification results can be slightly different from sum of the following breakdown for rounding of fractions.) Breakdown (by life cycle stage, by process, by flow, etc.) Raw material acquisition stage 610 kg-CO2e Raw material acquisition stage 48 kg-CO2e Production stage 48 kg-CO2e Use & maintenance stage 410 kg-CO2e Use & maintenance stage 410 kg-CO2e Value and description of additional info. Value to be stated on the mark Value to be stated on the mark 1,200 kg Per unit product Calculated in the following conditions; Disposal & recycling stage on the mark 0 Label on the mark 1,200 kg Per unit product	. CFI	P quantification results, an	nd contents of CFP declration	
Raw material acquisition stage 610 kg-CO2e Production stage 48 kg-CO2e Distribution stage 27 kg-CO2e Use & maintenance stage 410 kg-CO2e Disposal & recycling stage 76 kg-CO2e Value and description of additional info. Value to be stated on the mark Value to be stated on the mark 1,200 kg Per unit product Calculated in the following conditions; Disposal & recycling stage Calculated in the following conditions; Disposal & recycling stage		CFP quantification		(CFP quantification results can be slightly different from sum of the
stage 010 Ng=CO2e 3.2 Production stage 48 kg=CO2e Distribution stage 27 kg=CO2e Use & maintenance stage 410 kg=CO2e Disposal & recycling stage 76 kg=CO2e Value and description of additional info. Value to be stated on the mark Value to be stated on the mark 1,200 kg Per unit product Calculated in the following conditions; Disposal & recycling & the standard scenario for Multifunction Disposal & recycling		Breakdown (by life cycl	ele stage, by process, by flow, etc.)	
3.2 Distribution stage 27 kg-CO2e Use & maintenance stage 410 kg-CO2e Disposal & recycling stage 76 kg-CO2e Value and description of additional info. Value to be stated on the mark Image: Calculated in the following conditions; Disposal & recycling Calculated in the following conditions; Disposal & recycling			610	kg-CO ₂ e
Distribution stage 27 kg-CO2e Use & maintenance stage 410 kg-CO2e Disposal & recycling stage 76 kg-CO2e Value and description of additional info. Value and description of additional info. Value to be stated on the mark 1,200 kg Per unit product Calculated in the following conditions; Disposal & recycling • the standard scenario for Multifunction recycling	3.2	Production stage	48	kg-CO ₂ e
Disposal & recycling stage 76 kg-CO2e Value and description of additional info. Value and description of additional info. Value to be stated on the mark 1,200 kg Per unit product Calculated in the following conditions; Disposal & • the standard scenario for Multifunction recycling	0.2	Distribution stage	27	kg-CO ₂ e
Value and description of additional info. Value to be stated on the mark 1,200 kg Calculated in the following conditions; bisposal & - the standard scenario for Multifunction		Use & maintenance stage	410	kg-CO ₂ e
Value to be stated on the mark <numerial value=""> <value cfp="" mark="" on=""> Value to be stated on the mark 1,200 kg Per unit product Calculated in the following conditions; Disposal & - the standard scenario for Multifunction recycling</value></numerial>		. , , , ,	_	kg-CO ₂ e
Value to be stated on the mark 1,200 kg Per unit product Calculated in the following conditions; Disposal & - the standard scenario for Multifunction recycling		Value and description of a		
on the mark 1,200 kg Per unit product Calculated in the following conditions; Disposal - the standard scenario for Multifunction recycling		Value to be stated	<numerial value=""></numerial>	<value cfp="" mark="" on=""></value>
- the standard scenario for Multifunction			1,200 kg	Per unit product
3.3 Contents of additional	3.3		 the standard scenario for Mu Device (EP type), Print volume: 360,000 sheet US market, 	& ultifunction & recycling stage S, ered. Use & maintena nce stage 35% Asymptotic
3.4 Remarks —	3.4	Remarks		_

5	. Con	ditions of quantification			
	5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID PA-DG-02
	5.3				s preferentially used. Available secondary data 't correspond to basic data v.1.04.

6. Ver	ification information				
6.1	Verification method	CFP System certification	6.2	CFP system certification No.	SCN14002
6.3	Verification ID	CV-DG02-18053	6.4	Completion date of verification	1/24/2019

7. Prog	gram information				
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	http://www.cfp-japan.jp/
7.3	Program operator	Japan Environmental Management Association for Industry (JEMAI)	7.4	Address	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

|--|

(*) For secondary data, refer to the following page on the CFP website. http://www.cfp-japan.jp/calculate/verify/data.html