## Registration Information Carbon Footprint of Products (CFP)



1. Prod	duct information		
1.1	Registration number	CR-DG02-18037	1.7 Product photo
1.2	Registration name	Canon imageRUNNER ADVANCE C356iF III(For USA)	
1.3	Model name / number	Canon imageRUNNER ADVANCE C356iF III(For USA)	
1.4	Main specifications of product	Multifunction Copiers Print speed BW: 36 ppm / CL: 36 ppm (LTR) 511mm(W) × 651mm(D) × 639mm(H) Product weight: Approximately 49kg	- Table 1
1.5	CFP quantification unit	Per unit product	W W
1.6	CFP release date	4/4/2019	Cassette Feeding Unit is excluded.

2. Cor	npany Information	
2.1	Company name (in English)	Canon Inc.
2.2	Phone number (incl. area code)	+81-3-3758-2111

3. CFF	quantification results, an	d contents of CFP deciration	
3.1	CFP quantification results	1,600	$kg\text{-}CO_2e$ (CFP quantification results can be slightly different from sum of the following breakdown for rounding of fractions.)
	Breakdown (by life cycl	e stage, by process, by flow, etc.)	
	Raw material acquisition stage	410	kg-CO <sub>2</sub> e
3.2	Production stage	85	kg-CO₂e
5.2	Distribution stage	15	kg-CO₂e
	Use & maintenance stage	1,100	kg-CO₂e
	Disposal & recycling stage	45	kg-CO₂e
	Value and description of		
	Value to be stated	<numerial value=""></numerial>	<value cfp="" mark="" on=""></value>
	on the mark	1,600 kg	Per unit product
3.3	Contents of additional info.	Calculated in the following cor - the standard scenario for Mu Device (EP type), - Print volume: 768,000 sheets - US market, - Printing paper is not conside	& material acquisitio recycling acquisitio stage n stage 25%
3.4	Remarks		_

4 Into	. Interpretation of CFP quantification results			
4. Inter	rpretation of CFP quantility			
4.1	Interpretation of CFP quantification results	<ul> <li>CO2 emission in Use &amp; maintenance stage is the largest as 66%. It is important to save energy during product usage and to make the life time of consumables longer. The condition in this CFP evaluation can be different from the one which the user operates under. A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during Use &amp; maintenance stage.</li> <li>CO2 emission in Raw material acquisition stage is the second largest as 25%. It is also important to reduce the size and weight, and to use low environmental impact materials.</li> <li>We evaluated the CFP with Canon's own data of raw materials weight and the general basic unit for the parts because it is difficult to collect the data for a couple of thousands of parts. Accordingly, the results may be different from the specific product specification.</li> <li>As such, please be advised that this result would be a rough estimate.</li> </ul>		

Į.	5. Con	ditions of quantification			
	5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID PA-DG-02
	5.3				preferentially used. Available secondary data correspond to basic data v.1.04.

6. Ver	ification information				
6.1	Verification method	CFP System certification	6.2	CFP system certification No.	SCN14002
6.3	Verification ID	CV-DG02-18037	6.4	Completion date of verification	12/26/2018

7. Pro	gram information				
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	http://www.cfp-japan.jp/
7.3	Program operator	Japan Environmental Management Association for Industry (JEMAI)	7.4	Address	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

8	Remarks	_

<sup>(\*)</sup> For secondary data, refer to the following page on the CFP website. http://www.cfp-japan.jp/calculate/verify/data.html