Registration Information Carbon Footprint of Products (CFP)



1. Prod	1. Product information				
1.1	Registration number	CR-DG02-17081	1.7 Product photo		
1.2	Registration name	Canon imagePRESS C650 Printer (For USA)	and the second		
1.3	Model name / number	Canon imagePRESS C650 Printer (For USA)			
1.4	Main specifications of product	Multifunction Copiers Print speed BW: 65 ppm / CL: 65 ppm (LTR) 1806mm(W) × 934mm(D) × 1424mm(H) Product weight: Approximately 279.5kg			
1.5	CFP quantification unit	Per unit product	DUPLEX COLOR IMAGE		
1.6	CFP release date	Dec.22 2017	DUPLEX COLOR IMAGE		

2	2. Company Information		
	2.1	Company name (in English)	Canon Inc.
	2.2	Phone number (incl. area code)	+81-3-3758-2111

3. CFF	3. CFP quantification results, and contents of CFP declration				
3.1	CFP quantification results	4,500	$kg\text{-}CO_2e$ (CFP quantification results can be slightly different from sum of the following breakdown for rounding of fractions.)		
	Breakdown (by life cycl	e stage, by process, by flow, etc.)			
	Raw material acquisition stage	1,600	kg-CO ₂ e		
3.2	Production stage	140	kg-CO₂e		
5.2	Distribution stage	80	kg-CO ₂ e		
	Use & maintenance stage	2,500	kg-CO ₂ e		
	Disposal & recycling stage	140	kg-CO₂e		
	Value and description of a				
	Malua ta ba atatad	<numerial value=""></numerial>	<value cfp="" mark="" on=""></value>		
	Value to be stated on the mark	4,500 kg	Per unit product		
3.3	Contents of additional info.	Calculated in the following cor - the standard scenario for Mu Device (EP type), - Print volume: 2,534,400 shee - US market, - Printing paper is not conside	Raw recycling stage stage 3% acquisitio n stage 36%		
3.4	Remarks		_		

4. Interpretation of CFP quantification results						
4.1	Interpretation of CFP quantification results	CO2 emission in Use & maintenance stage is the largest as 56%. It is important to save energy during product usage and to make the life time of consumables longer. The condition in this CFP evaluation can be different from the one which the user operates under. A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during Use & maintenance stage. CO2 emission in Raw material acquisition stage is the second largest as 36%. It is also important to reduce the size and weight, and to use low environmental impact materials. We evaluated the CFP with Canon's own data of raw materials weight and the general basic unit for the parts because it is difficult to collect the data for a couple of thousands of parts. Accordingly, the results may be different from the specific product specification. As such, please be advised that this result would be a rough estimate.				

I	5. Conditions of quantification					
I	5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-02
	5.3		Basic secondary data v.1. is used if the items don't c			ailable secondary data v.1.01 01.

I	6. Verification information					
	6.1	Verification method	CFP System certification	6.2	CFP system certification No.	SCN14002
ĺ	6.3	Verification ID	CV-DG02-17050	6.4	Completion date of verification	11/28/2017

I	7. Program information					
	7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	http://www.cfp-japan.jp/
ĺ	7.3	Program operator	Japan Environmental Management Association for Industry (JEMAI)	7.4	Address	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

8	Remarks	_
U	remanes	

^(*) For secondary data, refer to the following page on the CFP website. http://www.cfp-japan.jp/calculate/verify/data.html