## Registration information of Carbon Footprint of Products

1. Pro	1. Product information					
1.1	Registration number	CR-DG01-13007	1.7 Product photo			
1.2	Product name	Color Multifunction Office Systems				
1.3	Product model	imageRUNNER ADVANCE C5235F				
1.4	Main specifications of product	Print speed (BW/CL): 35/30 ppm (A4) Paper size: A3 maximum Standardized automatic duplexing Functionality Standardized FAX Functionality 620mm(W)×712mm(D)×931mm(H) Product weight: Approximately 150kg	· · · · · · · · · · · · · · · · · · ·			
1.5	CFP quantification unit	Per unit product				
1.6	Date of release	01/25/2013	Double cassette feeding unit is excluded.			

2. Cor	2. Company Information				
2.1	Company name	Canon Inc.			
2.2	Phone number	+81-3-3758-2111			

3. CFF	quantification results, an	d contents of CFP decIration			
3.1	CFP quantification results	2200	$kg\text{-}CO_2\text{e}$ (CFP quantification results can be slightly different from sum of the following breakdown for rounding of fractions.)	е	
	Breakdown (by life cycle stage, by process, by flow, etc.)				
	Raw material acquisition stage	880	kg-CO₂e		
	Production stage	110	kg-CO₂e		
3.2	Distribution stage	42	kg-CO₂e		
	Use & maintenance stage	1000	kg-CO <sub>2</sub> e		
	Disposal & recycling stage	120	kg-CO₂e		
	Value in a mark, and co				
		<contents></contents>	<unit a="" for="" in="" mark="" the="" value=""></unit>		
	Value in a mark	2,200kg	Per unit product		
3.3	Contents of additional info.	●The CO <sub>2</sub> emissions from the control excluded in 3.1.  ●Scenario: Multifunction Device excluded in 3.1.  ●Scenario: Multifunction Device excluded in 3.1.  ●Scenario: Multifunction Device excluded in 3.1.  ●CO <sub>2</sub> emission of Distribution sometimed by the shipping ratio.  ●Print volume: 730,000 sheets.  ●In this scenario, the CO <sub>2</sub> emiss papers are estimated 6,600kg-CA4 paper.  ●280kg-CO <sub>2</sub> e of the CO <sub>2</sub> emiss (approximately 13%) can be reconstructed in applied to 365,000 sheet volume). 1,700kg-CO <sub>2</sub> of the CO <sub>2</sub> from the copy papers can also be	Disposal Raw recycling mater acquisi n stage stage is  Signature of the production o	rial itio ge	
3.4	Remarks	CFP quantification results[kg-CO <sub>2</sub> e]=1.51 E-03×print volume[sheets]+1.07 E+03 (more than 50,000 sheets)			

4. Inte	4. Interpretation of CFP quantification results					
4.1	Interpretation of CFP quantification results	CO2 emission in Use & maintenance stage is the largest as 46%. It is important to save energy during product usage. The use condition in this scenario can be different from the use condition of the user.  A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during product usage. For example, 280kg-CO2e of the CO2 emissions (approximately 13%) can be reduced if 2-in-1 print is applied to 365,000 sheets (50%of print volume).  CO2 emission in Raw material acquisition stage is the second largest as 41%. It is also important to reduce size and weight.  Primary data is used in the raw material consumption. Secondaty data is used in the parts manufactureing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts.  Please understand this result as a rough estimate according to the reason mentioned above.				

5. Cor	5. Conditions of quantification				
5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-01
5.3		Basic secondary data v.1.01 is preferentially used. Available secondary data v.1.01 is used if the items don't correspond to basic data v.1.01.			

6. Verification information					
6.1	Verification method	Product-by-product	6.2	CFP system certification No.	-
6.3	Verification ID	CV-DG01-13007	6.4	Valid period of verification	01/23/2016

7	Remarks	(The secretariat use)
---	---------	-----------------------

<sup>(\*)</sup> For secondary data, refer to the following page on the CFP website. http://www.cfp-japan.jp/calculate/verify/data.html