Registration information of Carbon Footprint of Products

1. Product information					
1.1	Registration number	CR-DG01-13006	1.7 Product photo		
1.2	Product name	Color Multifunction Office Systems			
1.3	Product model	imageRUNNER ADVANCE C5240F			
1.4	Main specifications of product	Print speed (BW/CL): 40/35 ppm (A4) Paper size: A3 maximum Standardized automatic duplexing Functionality Standardized FAX Functionality 620mm(W)×712mm(D)×931mm(H) Product weight: Approximately 150kg			
1.5	CFP quantification unit	Per unit product			
1.6	Date of release	01/25/2013	Double cassette feeding unit is excluded.		
2. Company Information					

2. Cor	2. Company Information				
2.1	Company name	Canon Inc.			
2.2	Phone number	+81-3-3758-2111			

3. CFP guantification results, and contents of CFP declration					
3.1	CFP quantification results	2400	kg-CO ₂ e (CFP quantification re following breakdown		different from sum of the ons.)
	Breakdown (by life cycle stage, by process, by flow, etc.)				
3.2	Raw material acquisition stage	890	kg-CO ₂ e		
	Production stage	100	kg-CO ₂ e		
	Distribution stage	42	kg-CO ₂ e		
	Use & maintenance stage	1200	kg-CO ₂ e		
	Disposal & recycling stage	120	kg-CO ₂ e		
	Value in a mark, and co	ntents of additional info.	•		
		<contents></contents>	<ur< td=""><td colspan="2"><unit a="" for="" in="" mark="" the="" value=""></unit></td></ur<>	<unit a="" for="" in="" mark="" the="" value=""></unit>	
3.3	Value in a mark	2,400kg	Per unit product		luct
	Contents of additional info.	 The CO₂ emissions from the dexcluded in 3.1. Scenario: Multifunction Device Sales area: around the world. CO₂ emission of Distribution sequantified by the shipping ratio. Print volume: 960,000 sheets. In this scenario, the CO₂ emission are estimated 8,700kg-CA4 paper. 330kg-CO₂e of the CO₂ emission (approximately 14%) can be recorded by the shipping the course of the course	e (EP type) stage is ssions from copy CO2e at 4.0g per sions duced if 2-in-1 ts (50%of print O2 emissions	Disposal & recycling stage 5% Use & maintena nce stage 51%	Raw material acquisitio n stage 38% Productio n stage Distributi 4% on stage 2%
3.4	Remarks	CFP quantification results[kg-CO ₂ e]=1.36 E-03×print volume[sheets]+1.08 E+03 (more than 50,000 sheets)			

4. Interpretation of CFP quantification results					
4.1	Interpretation of CFP	CO2 emission in Use & maintenance stage is the largest as 51%. It is important to save energy during product usage. The use condition in this scenario can be different from the use condition of the user. A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during product usage. For example, 330kg-CO2e of the CO2 emissions (approximately 14%) can be reduced if 2-in-1 print is applied to 480,000 sheets (50%of print volume). CO2 emission in Raw material acquisition stage is the second largest as 38%. It is also important to reduce size and weight. Primary data is used in the raw material consumption. Secondaty data is used in the parts manufactureing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as a rough estimate according to the reason mentioned above.			

5. Conditions of quantification					
5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-01
5.3		Basic secondary data v.1 v.1.01 is used if the items			

6. Verification information					
6.1	Verification method	Product-by-product	6.2	CFP system certification No.	-
6.3	Verification ID	CV-DG01-13006	6.4	Valid period of verification	01/23/2016

7	Remarks	(The secretariat use)

(*) For secondary data, refer to the following page on the CFP website. http://www.cfp-japan.jp/calculate/verify/data.html