Registration information of Carbon Footprint of Products

1. Product information					
1.1	Registration number	CR-DG01-12004-1	1.7 Product photo		
1.2	Product name	Color Multifunction Office Systems			
1.3	Product model	imageRUNNER ADVANCE C5255	- Comp		
1.4	Print speed (BW/CL): 55/51 ppm (A4) Paper size: A3 maximum Standardized automatic duplexing Functionality 620mm(W)×715mm(D)×950mm(H) Product weight: Approximately 153kg		9 5		
1.5	CFP quantification unit	Per unit product	0		
1.6	Date of release	12/4/2012	Double cassette feeding unit is excluded.		

2. Company Information				
2.1	Company name	Canon Inc.		
2.2	Phone number	+81-3-3758-2111		

3. CFF	quantification results, and	d contents of CFP decIration					
3.1	CFP quantification results	3200	` '	esults can be slightly diffe			
	Breakdown (by life cycl	Breakdown (by life cycle stage, by process, by flow, etc.)					
	Raw material acquisition stage	900	kg-CO ₂ e				
	Production stage	100	kg-CO ₂ e				
3.2	Distribution stage	43	kg-CO₂e				
	Use & maintenance stage	2000	kg-CO₂e				
	Disposal & recycling stage	130	kg-CO₂e				
	Value in a mark, and co	ntents of additional info.					
		<contents></contents>	<ur< td=""><td>nit for the value in a</td><td>mark></td></ur<>	nit for the value in a	mark>		
	Value in a mark	3,200kg		Per unit product			
3.3	Contents of additional info.	●The CO2 emissions from the control excluded in 3.1. ●Scenario: Multifunction Device ●Sales area: around the world. ●CO2 emission of Distribution superitied by the shipping ratio. ●Print volume: 1,805,000 sheet ●In this scenario, the CO2 emistic papers are estimated 16,000kg-per A4 paper. ●530kg-CO2e of the CO2 emistic (approximately 16%) can be redured print is applied to 902,500 sheet volume). 4,100kg-CO2 of the CO2 from the copy papers can also be	(EP type) tage is s. sions from copy CO2e at 4.0g tions uced if 2-in-1 s (50%of print 2 emissions	Disposal & recycling stage 4% Use & maintena nce stage 63%	Raw material acquisitio n stage 29% Productio n stage 3% Distributi on stage 1%		
3.4	Remarks	CFP quantification results[kg-CO₂e]=1.17 E-03×print volume[sheets]+1.10 E+03 (more than 50,000 sheets)					

4. Interpretation of CFP quantification results				
4.1	Interpretation of CFP quantific quantification results	CO2 emission in Use & maintenance stage is the largest as 63%. It is important to save energy during product usage. The use condition in this scenario can be different from the use condition of the user. A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during product usage. For example, 530kg-CO2e of the CO2 emissions (approximately 16%) can be reduced if 2-in-1 print is applied to 902,500 sheets (50%of print volume). CO2 emission in Raw material acquisition stage is the second largest as 29%. It is also important to reduce size and weight. Primary data is used in the raw material consumption. Secondaty data is used in the parts manufactureing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as a rough estimate according to the reason mentioned above.		

5. Con	5. Conditions of quantification				
5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-01
5.3		Basic secondary data v.1.01 is preferentially used. Available secondary data v.1.01 is used if the items don't correspond to basic data v.1.01.			

6. Veri	6. Verification information				
6.1	Verification method	Product-by-product	6.2	CFP system certification No.	-
6.3	Verification ID	CV-DG01-12004	6.4	Valid period of verification	11/11/2015

I	7	Remarks	01/24/2013 Registration information 3. and 4 are modified.

^(*) For secondary data, refer to the following page on the CFP website. http://www.cfp-japan.jp/calculate/verify/data.html