Registration Information Carbon Footprint of Products (CFP)

1. Product information						
1.1	Registration number	CR-DG01-16047-A	1.7 Product photo			
1.2	Registration name	DocuCentre-V C7785 (For Japan)				
1.3	Model name / number DocuCentre-V C7785					
1.4	Main specifications of product	Print speed (Color/Mono): 70ppm/75ppm Paper size: SRA3(320x450mm) maximum Capable of duplex printing, facsimile and scanning Product Size: 700(W)x804(D)x1154(H) (mm) Product weight: 240kg				
1.5	CFP quantification unit	Per unit product				
1.6	CFP release date	2016/7/12				

2.	2. Company Information					
	2.1 Company name (in English) FUJIFILM Business Innovation Corp.					
2	.2	Phone number (incl. area code)	+81-3-6271-5111			

3. CFF	3. CFP quantification results, and description of CFP declration				
3.1	CFP quantification results	6,200	kg-CO2e		
	Breakdown (by life cycle stage, by process, by flow, etc.)				
	Raw material acquisition stage	1,300	kg-CO₂e		
3.2	Production stage	100	kg-CO₂e		
3.2	Distribution stage	43	kg-CO₂e		
	Use & maintenance stage	4,700	kg-CO₂e		
	Disposal & recycling stage	63	kg-CO₂e		
	Value in CFP mark and description of additional info.				
		<numerial value=""></numerial>	<unit for="" the="" value=""></unit>		
	Value in CFP mark	6,200 kg	per unit product		
3.3	Description of additional info.	*Calculated by the standard So *CO ₂ emission in the distribution assumes Japan as the main sales area. *Electric power in the use and maintenance stage is evaluated the public electric-power-consurate in Japan. *The CO ₂ emission due to prin paper is excluded from the use and maintenance stage. *Print volume is assumed 2,94	an stage and with amption are production stage and Distribution stage and Distribution stage and Distribution stage and Disposal & recycling stage and Disposal & recycling stage		
3.4	Remarks	*Print volume: 2,940,000 sheets *In this scenario, the $\rm CO_2$ emissions from copy papers are estimated 23,000 kg- $\rm CO_2$ e at 4.0 g per A4 paper.			

4. Interpretation of CFP quantification results					
4.1	Interpretation of CFP quantification results	CO2 emission in use and maintenance stage is the largest as 76%. It is important to save energy during product usage. The use condition in this scenario can be different from the use condition of the user. A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during product usage. For example, 1,170kg-CO2e of the CO2 emissions (approximately 19%) can be reduced if 2-in-1 print is applied to 1,470,000sheets (50% of print volume). Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as the rough estimate according to the reason mentioned above.			
5. Con	nditions of quantification				
5.1		Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-01
5.3	Assumptions of secondary data used	Basic secondary data v.1.01 is preferertially used. Available secondary data (country v.1.04, foreign country v.1.01) is used if the items don't correspond to basic data v.1.01.			
6. Veri	ification information				
6.1	Verification method	Product-by-product	6.2	CFP system certification No.	_

Ο.	o. Volinication information					
	6.1	Verification method	Product-by-product	6.2	CFP system certification No.	-
	6.3	Verification ID	CV-DG01-16047	6.4	Completion date of verification	2016年7月5日

7. Pro	7. Program information				
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	http://www.cfp-japan.jp/
7.3	Program operator	Japan Environmental Management Association for Industry (JEMAI)	7.4	Address	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

8	Remarks	Revised on April 1st, 2021: Implemented the company name change.
_	rtomanto	

For secondary data, please refer to the information on the following CFP website. http://www.cfp-japan.jp/calculate/verify/data.html