Registration Information Carbon Footprint of Products (CFP)



1. Pro	duct information		
1.1	Registration number	CR-DG02-17071-A	1.7 Product photo
1.2	Registration name	Xerox VersaLink C605 Color Multifunction Printer	To come
1.3	Model name / number	Xerox VersaLink C605 Color Multifunction Printer	
1.4	Print speed (Color/Mono): 55ppm/55ppm (Letter) Maximum Paper size: Legal(215.9×355.6mm) Capable of print/copy/scan/fax, duplex printing, NFC. Product Size: 470.0(W)x502.8(D)x643.7(H) (mm) Product weight: 36.1kg		
1.5	CFP quantification unit	Per unit product	
1.6	CFP release date	July 14th, 2017	

2. Company Information				
	2.1	Company name (in English)	FUJIFILM Business Innovation Corp.	
ſ	2.2	Phone number (incl. area code)	+81-3-6271-5111	

3. CFF	o quantification results, an	d description of CFP declration	
3.1	CFP quantification results	3,400	kg-CO2e
	Breakdown (by life cyc	e stage, by process, by flow, etc.)	
	Raw material acquisition stage	270	kg-CO₂e
	Production stage	5.1	kg-CO ₂ e
3.2	Distribution stage	29	kg-CO ₂ e
	Use & maintenance stage	3,000	kg-CO ₂ e
	Disposal & recycling stage	20	kg-CO ₂ e
	Value in CFP mark and d	escription of additional info.	
		<numerial value=""></numerial>	<unit for="" the="" value=""></unit>
	Value in CFP mark	3,400kg	per unit product
3.3	Description of additional info.	*Calculated by the standard Scenario for MFP (EP type). *CO ₂ emission in the distribution stage assumes the United States as the massales area. *Electric power in the use and maintenance stage is evaluated with the public electric-power-consumption-rate in the United States. *Print volume is assumed 1,815,000 sheets. *In this scenario, the CO ₂ emissions from copy papers are estimated 14,000 CO ₂ e at 4.0g per A4 paper. *The CO ₂ emission of printing paper is excluded from the use and maintenar stage. Disposal & recycling stage 1% Production stage 0.2% Distribution stage 1%	
2.4	Domorko		
3.4	Remarks		

4. Inte	4. Interpretation of CFP quantification results				
4. Inte	Interpretation of CFP	CO2 emission in use and maintenance stage is the largest as 90%. It is important to save energy during product usage. The use condition in this scenario can be different from the use condition of the user. A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during product usage. For example, 760kg-CO2e of the CO2 emissions (approximately 23%) can be reduced if 2-in-1 print is applied to 907,500 sheets (50% of the estimated total print volume).			
		Primary data is used in the raw material consumption. Secondary data is used in the parts manufacturing process which might not be reflected our own circumstances because it is difficult to collect the data for thousands of the parts. Please understand this result as the rough estimate according to the reason mentioned above.			

	5. Con	onditions of quantification				
	5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID	PA-DG-02
ľ	5.3	Assumptions of	Basic secondary data v.1.01 is preferentially used. Available secondary data (country v.1.04, foreign country v.1.01) is used if the items don't correspond basic data v.1.01.			

6. Ver	Verification information				
6.1	Verification method	Product-by-product	6.2	CFP system certification No.	_
6.3	Verification ID	CV-DG02-17071	6.4	Completion date of verification	July 10th, 2017

7. Pro	7. Program information				
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	http://www.cfp-japan.jp/
7.3	Program operator	Japan Environmental Management Association for Industry (JEMAI)	7.4	Δαατρος	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

I	8	Remarks	Revised on April 1st. 2021: Implemented the company name change.
		Remarks	revised on April 13t, 2021. Implemented the company hame change.

For secondary data, please refer to the information on the following CFP website. http://www.cfp-japan.jp/calculate/verify/data.html