## Registration Information Carbon Footprint of Products (CFP)



1. Pro	1. Product information					
1.1	Registration number	CR-DG02-19009	1.7 Product photo			
1.2	Registration name	Canon imageRUNNER ADVANCE C5535i III(For USA)				
1.3	Model name / number	Canon imageRUNNER ADVANCE C5535i III(For USA)				
1.4	Main specifications of product	Multifunction Copiers Print speed BW: 35 ppm / CL: 35 ppm (LTR) 620mm(W) × 742mm(D) × 950mm(H) Product weight: Approximately 141kg	Com			
1.5	CFP quantification unit	Per unit product				
1.6	CFP release date	4/4/2019	Cassette Feeding unit is excluded.			

2. Company Information				
2.1	Company name (in English)	Canon Inc.		
2.2	Phone number (incl. area code)	+81-3-3758-2111		

3. CFF	o quantification results, an	d contents of CFP declration		
3.1	CFP quantification results	1,500	$\mbox{kg-CO}_2\mbox{e}$ (CFP quantification results can be slightly different from sum of the following breakdown for rounding of fractions.)	
	Breakdown (by life cycle stage, by process, by flow, etc.)			
	Raw material acquisition stage	880	kg-CO₂e	
3.2	Production stage	89 kg-CO₂e		
3.2	Distribution stage	35 kg-CO₂e		
	Use & maintenance stage	390	kg-CO₂e	
	Disposal & recycling stage	99	kg-CO <sub>2</sub> e	
	Value and description of			
	Males to be atotal	<numerial value=""></numerial>	<value cfp="" mark="" on=""></value>	
	Value to be stated on the mark	1,500 kg	Per unit product	
3.3	Contents of additional info.	Calculated in the following control of the standard scenario for M Device (EP type), - Print volume: 729,600 shee - US market, - Printing paper is not consider	& recycling stage ts, Use &	
3.4	Remarks		_	

4. Inte	Interpretation of CFP quantification results		
		•CO2 emission in Raw material acquisition stage is the largest as 59%. It is important to reduce the size and weight, and to use low environmental impact materials.	
4.1	Interpretation of CFP quantification results	•CO2 emission in Use & maintenance stage is the second largest as 26%. It is also important to save energy during product usage and to make the life time of consumables longer. The condition in this CFP evaluation can be different from the one which the user operates under. A choice of the use condition (print mode, print conditions and so on) can reduce the CO2 emission during Use & maintenance stage.	
		•We evaluated the CFP with Canon's own data of raw materials weight and the general basic unit for the parts because it is difficult to collect the data for a couple of thousands of parts. Accordingly, the results may be different from the specific product specification.	
		As such, please be advised that this result would be a rough estimate.	

5	5. Conditions of quantification				
	5.1	Name of approved CFP-PCR	Imaging input and/or output equipment	5.2	Approved CFP-PCR ID PA-DG-02
	5.3				preferentially used. Available secondary data correspond to basic data v.1.04.

6. Verification information					
6.1	Verification method	CFP System certification	6.2	CFP system certification No.	SCN14002
6.3	Verification ID	CV-DG02-19009	6.4	Completion date of verification	3/15/2019

7. Program information					
7.1	Program name	Carbon Footprint Communication Program	7.2	Web site	http://www.cfp-japan.jp/
7.3	Program operator	Japan Environmental Management Association for Industry (JEMAI)	7.4	Δαατρος	2-1, Kajicho 2-chome, Chiyoda-ku, Tokyo 101-0044

8	Remarks	_
---	---------	---

<sup>(\*)</sup> For secondary data, refer to the following page on the CFP website. http://www.cfp-japan.jp/calculate/verify/data.html